

Y. Efendiev, O. Iliev, C. Kronsbein

Multi-level Monte Carlo methods using ensemble level mixed MsFEM for two-phase flow and transport simulations

© Fraunhofer-Institut für Techno- und Wirtschaftsmathematik ITWM 2012

ISSN 1434-9973

Bericht 217 (2012)

Alle Rechte vorbehalten. Ohne ausdrückliche schriftliche Genehmigung des Herausgebers ist es nicht gestattet, das Buch oder Teile daraus in irgendeiner Form durch Fotokopie, Mikrofilm oder andere Verfahren zu reproduzieren oder in eine für Maschinen, insbesondere Datenverarbeitungsanlagen, verwendbare Sprache zu übertragen. Dasselbe gilt für das Recht der öffentlichen Wiedergabe.

Warennamen werden ohne Gewährleistung der freien Verwendbarkeit benutzt.

Die Veröffentlichungen in der Berichtsreihe des Fraunhofer ITWM können bezogen werden über:

Fraunhofer-Institut für Techno- und Wirtschaftsmathematik ITWM Fraunhofer-Platz 1

67663 Kaiserslautern Germany

Telefon: +49(0)631/31600-4674
Telefax: +49(0)631/31600-5674
E-Mail: presse@itwm.fraunhofer.de
Internet: www.itwm.fraunhofer.de

## Vorwort

Das Tätigkeitsfeld des Fraunhofer-Instituts für Techno- und Wirtschaftsmathematik ITWM umfasst anwendungsnahe Grundlagenforschung, angewandte Forschung sowie Beratung und kundenspezifische Lösungen auf allen Gebieten, die für Techno- und Wirtschaftsmathematik bedeutsam sind.

In der Reihe »Berichte des Fraunhofer ITWM« soll die Arbeit des Instituts kontinuierlich einer interessierten Öffentlichkeit in Industrie, Wirtschaft und Wissenschaft vorgestellt werden. Durch die enge Verzahnung mit dem Fachbereich Mathematik der Universität Kaiserslautern sowie durch zahlreiche Kooperationen mit internationalen Institutionen und Hochschulen in den Bereichen Ausbildung und Forschung ist ein großes Potenzial für Forschungsberichte vorhanden. In die Berichtreihe werden sowohl hervorragende Diplom- und Projektarbeiten und Dissertationen als auch Forschungsberichte der Institutsmitarbeiter und Institutsgäste zu aktuellen Fragen der Techno- und Wirtschaftsmathematik aufgenommen.

Darüber hinaus bietet die Reihe ein Forum für die Berichterstattung über die zahlreichen Kooperationsprojekte des Instituts mit Partnern aus Industrie und Wirtschaft.

Berichterstattung heißt hier Dokumentation des Transfers aktueller Ergebnisse aus mathematischer Forschungs- und Entwicklungsarbeit in industrielle Anwendungen und Softwareprodukte – und umgekehrt, denn Probleme der Praxis generieren neue interessante mathematische Fragestellungen.

Prof. Dr. Dieter Prätzel-Wolters Institutsleiter

Kaiserslautern, im Juni 2001

# Multi-level Monte Carlo methods using ensemble level mixed MsFEM for two-phase flow and transport simulations

Y. Efendiev\* O. Iliev<sup>†</sup> C. Kronsbein<sup>‡</sup>
May 30, 2012

### Abstract

In this paper, we propose multi-level Monte Carlo (MLMC) methods that use ensemble level mixed multiscale methods in the simulations of multi-phase flow and transport. The main idea of ensemble level multiscale methods is to construct local multiscale basis functions that can be used for any member of the ensemble. We consider two types of ensemble level mixed multiscale finite element methods, (1) the no-localsolve-online ensemble level method (NLSO) and (2) the local-solve-online ensemble level method (LSO). Both mixed multiscale methods use a number of snapshots of the permeability media to generate a multiscale basis. As a result, in the offline stage, we construct multiple basis functions for each coarse region where basis functions correspond to different realizations. In the no-local-solve-online ensemble level method one uses the whole set of pre-computed basis functions to approximate the solution for an arbitrary realization. In the local-solve-online ensemble level method one uses the pre-computed functions to construct a multiscale basis for a particular realization. With this basis the solution corresponding to this particular realization is approximated in LSO mixed MsFEM. In both approaches the accuracy of the method is related to the number of snapshots computed based on different realizations that one uses to pre-compute a multiscale basis. We note that LSO approaches share similarities with reduced basis methods [11, 21, 22].

In multi-level Monte Carlo methods ([14, 13]), more accurate (and expensive) forward simulations are run with fewer samples while less accurate (and inexpensive) forward simulations are run with a larger number of samples. Selecting the number of expensive and inexpensive simulations

<sup>\*</sup>Department of Mathematics, Texas A&M University, College Station, TX 77843-3368. email: efendiev@math.tamu.edu. Corresponding author

 $<sup>^\</sup>dagger Fraunhofer$  ITWM & University of Kaiserslautern, 67663 Kaiserslautern, Germany. email: iliev@itwm.fraunhofer.de

 $<sup>^{\</sup>ddagger}$ Fraunhofer ITWM & University of Kaiserslautern, 67663 Kaiserslautern, Germany. email: kronsbein@itwm.fraunhofer.de

carefully, one can show that MLMC methods can provide better accuracy at the same cost as MC methods.

In our simulations, our goal is twofold. First, we would like to compare NLSO and LSO mixed MsFEMs. In particular, we show that NLSO mixed MsFEM is more accurate compared to LSO mixed MsFEM. Further, we use both approaches in the context of MLMC to speed-up MC calculations. We present basic aspects of the algorithm and numerical results for coupled flow and transport in heterogeneous porous media.

## 1 Introduction

Multi-phase flow and transport simulations in heterogeneous subsurface formations are challenging due to a rich hierarchy of spatial scales and uncertainties. Typical approaches include upscaling or multiscale methods where the solution is approximated on a coarse grid [8, 12]. In these simulations, effective media properties or multiscale basis functions are constructed for each coarsegrid block and they are used to inexpensively solve the problem on a coarse grid. Coarse-grid simulations help to reduce the computational cost; however, they can still be very expensive for stochastic problems due to the number of Monte Carlo (MC) simulations that are needed to make accurate predictions. Indeed, each MC simulation requires a coarse-grid parameter calculations that can be expensive, especially when one needs to generate relative permeabilities or other nonlinear constitutive relations. For this reason, various techniques are proposed to reduce the number of simulations in Monte Carlo methods. These approaches include ensemble level upscaling [7] or multiscale methods [3] that use fewer samples to compute effective properties for the whole ensemble. It is expensive to apply multiscale methods directly because basis functions need to be computed for each realization.

In this paper, we discuss two ensemble level mixed multiscale finite element methods (1) the no-local-solve-online (NLSO) and (2) the local-solve-online ensemble level method (LSO). The main idea of the ensemble level methods is to pre-compute multiscale basis functions using a number of permeability realizations. In the offline stage, in each coarse-grid block, we compute multiscale basis functions by selecting some realizations from the ensemble. Using these multiscale basis functions, our goal is to approximate the solution for an arbitrary realization. In the LSO method we use the pre-computed functions to build a multiscale basis in each coarse block for each arbitrary realization at the online stage. This approach entails of solving a local problem at the online stage and, therefore, we call it the local-solve-online mixed MsFEM. For the local problems we have to impose boundary conditions. The main idea of NLSO is to use all pre-computed basis functions to construct a coarse grid approximation. This approach does not compute a new multiscale basis function at the online stage and instead solves a larger coarse-grid system using all pre-computed multiscale basis functions.

The advantage of NLSO approaches is more evident if limited global information [4] is used to construct multiscale basis functions. As it was shown

(e.g., [4]), one can use single-phase flow information to construct multiscale basis functions and this can provide several-fold improvement in the accuracy in two-phase flow simulations. In online stage one needs boundary conditions for basis functions in the case of LSO. On the other hand, NLSO does not require any local solves and thus we can take an advantage of accurate multiscale basis functions computed for selected realizations. For LSO, even if multiscale basis functions at the offline stage are computed with limited global information, in the online stage, we impose local boundary conditions which affect the accuracy of the solution as we show in the paper. Note that LSO approaches are less expensive and thus we consider them.

In both methods the accuracy of the approximation of the solution for an arbitrary realization depends on the dimension of the pre-computed basis space. The more multiscale basis functions we pre-compute the more accurate is the approximation. In NLSO, one does not need to generate a coarse space for each new selected realization and simply projects the global solution onto the ensemble level multiscale space. For both method, NLSO and LSO, respectively, we consider boundary conditions for the pre-computation which use local or global information. We compare the NLSO and the LSO methods in terms of accuracy.

We apply the ensemble level methods in the framework of multi-level Monte Carlo methods (MLMC) to reduce the computational costs in comparison with a Monte Carlo method. Multi-level Monte Carlo, introduced by Heinrich ([15]) and later applied to stochastic ODEs by Giles ([14, 13]), and PDEs with stochastic coefficients by Schwab et al.([6]) and Cliffe et al. ([10]). The main idea of multi-level Monte Carlo (MLMC) is to use a number of samples at different levels to compute the expected values of quantities of interest. In these techniques, more realizations are used at the coarsest level with inexpensive forward computations. At the same time, fewer samples are used at the finest, most expensive to compute level. Combining the results of these computations by choosing the number of realizations at each level carefully, one can speed-up the computations. In this paper, we take the dimension of the multiscale space to be variable in MLMC.

In this paper, we take different numbers of samples to generate the multi-scale space. We show that the NLSO mixed MsFEM using global information gives more accurate approximation than the LSO mixed MsFEM. More forward coarse-grid simulations are run using the smaller dimensional multiscale spaces while less simulations are run using higher dimensional multiscale spaces. We show that by combining these simulation results in a MLMC framework one can achieve better accuracy for the same cost as MC. For this combination, one needs to know the convergence of ensemble level methods with respect to the coarse space dimension, respectively. One can estimate this rate based on a small number of apriori computations as discussed in the paper.

We present numerical results where single-phase flow and transport as well as two-phase flow and transport are tested. Permeability fields in our simulations are described by two-point correlation functions and parameterized using Karhunen-Loève expansion. In the simulations, we compare saturation profiles

at certain time instants and run MC computations on the finest coarse model such that the cost of MC and MLMC computations are the same. Our numerical results show that one can achieve higher accuracy when MLMC is used. We also compare the accuracy of NLSO and LSO mixed MsFEM. Though LSO mixed MsFEM is computationally more efficient, it is less accurate compared to NLSO mixed MsFEM.

The paper is organized as follows. In the next section, we present the model problem and the mixed multiscale finite element method. In Section 3 we introduce the ensemble level mixed MsFEMs, no-local-solve-online (NLSO) and local-solve-online ensemble level mixed MsFEM (LSO). Section 4 is devoted to MLMC using multiscale methods. We present numerical results in Section 5.

## 2 Preliminaries

In this paper, we will consider two-phase flow and transport in a porous media under the assumption that the displacement is dominated by viscous effects; i.e., we neglect the effects of gravity, compressibility, and capillary pressure. The two phases will be referred to as water and oil, designated by subscripts w and o, respectively. The governing equations describing this system are given by coupled pressure and saturation equations (saturation for the water phase)

$$-\operatorname{div}(\lambda(S)k\nabla p) = q_w + q_o, \tag{2.1}$$

$$\phi \frac{\partial S}{\partial t} + \nabla (vf(S)) = q_w, \qquad (2.2)$$

where  $\lambda$  is the total mobility, f(S) is the flux function, and v is the total velocity, which are

$$\lambda(S) = \frac{k_{rw}(S)}{\mu_w} + \frac{k_{ro}(S)}{\mu_o}, \quad f(S) = \frac{k_{rw}(S)}{\mu_w \lambda(S)}, \quad v = -\lambda(S)k \cdot \nabla p, \tag{2.3}$$

where S is the water saturation (volume fraction), p is pressure,  $q_w$  and  $q_o$  are volumetric source terms for water and oil, and  $\phi$  is the porosity. Here,  $k_{rw}(S)$  and  $k_{ro}(S)$  are relative permeabilities of water and oil phases that appear in Darcy's law for each phase  $v_j = -\frac{k_{rj}(S)}{\mu_j}k \cdot \nabla p$ , where  $v_j$  is the phase velocity, k is the permeability tensor and  $\mu_j$  is the phase viscosity. We use a single set of relative permeability curves.

## 2.1 Mixed multiscale finite element methods

In this section, we discuss mixed multiscale finite element methods (MsFEM) following [2, 12]. We write the two-phase flow equation as

$$(\lambda k)^{-1}v + \nabla p = 0$$
 in  $\Omega$   
 $\operatorname{div}(v) = q$  in  $\Omega$   
 $\lambda k \nabla p \cdot n = q$  on  $\partial \Omega$ . (2.4)

We assume Neumann boundary conditions.

Let  $V_h \subset H(\operatorname{div},\Omega)$  and  $Q_h \subset L^2(\Omega)/R$  be finite dimensional spaces and  $V_h^0 = V_h \cap H_0(\operatorname{div},\Omega)$ , where  $H_0(\operatorname{div},\Omega)$  is  $H(\operatorname{div},\Omega)$  with homogeneous boundary conditions. The numerical approximation of (2.4) on the fine grid is to find  $\{v_h, p_h\} \in V_h \times Q_h$  such that  $v_h \cdot n = g_h$  on  $\partial\Omega$  and

$$((\lambda k)^{-1}v_h, u_h) - (\operatorname{div} u_h, p_h) = 0 \quad \forall u_h \in V_h^0 (\operatorname{div} v_h, b_h) = (q, b_h) \quad \forall b_h \in Q_h,$$
 (2.5)

with the usual  $L^2$  inner product,  $(\cdot, \cdot)$ .

In a mixed MsFEM one attempts to design the approximation space for velocity in such a way that it contains the small-scale features of the solution. In a mixed MsFEM, the velocity field is approximated using multiscale basis functions, while piecewise constant functions are used to approximate the pressure field. In particular, these multiscale basis functions for the velocity field are constructed for each edge (face) of every block. Let  $\bigcup K_i = \Omega$  be a partitioning of the domain in polyhedral elements. We denote with  $\mathcal I$  the multi index set of pairs of indices of two neighboring blocks, i.e if  $K_i \cap K_{i'} \neq \emptyset$ ,  $\iota = \{ii'\} \in \mathcal I$ . We denote the interface of two neighboring blocks  $K_i$  and  $K_{i'}$  with  $\Gamma_\iota$ , i.e  $\Gamma_\iota$  is a common edge or a face of the blocks  $K_i$  and  $K_{i'}$ .

With a given permeability field k, we compute the corresponding multiscale basis function for  $\Gamma_{\iota}$  in the following way.

First we compute a function  $w_{\iota,k}$  by solving the following equation:

$$(-\operatorname{div}(k(x)\nabla w_{\iota,k}))|_{K_{i}} = \begin{cases} \frac{1}{|K_{i}|} & \text{if } \int_{K_{i}} q = 0\\ \frac{q}{\int_{K_{i}} q} & \text{else,} \end{cases}$$

$$(-\operatorname{div}(k(x)\nabla w_{\iota,k}))|_{K_{i'}} = \begin{cases} \frac{-1}{|K_{i'}|} & \text{if } \int_{K_{i'}} q = 0\\ \frac{-q}{\int_{K_{i'}} q} & \text{else,} \end{cases}$$

$$(2.6)$$

$$-k(x)\nabla w_{\iota,k} \cdot n_{ii'} = \begin{cases} g_{\iota} & \text{on } \Gamma_{\iota}\\ 0 & \text{else,} \end{cases}$$

where the choice of  $g_{\iota}$  will be discussed later and  $n_{ii'}$  is the normal pointing from  $K_i$  to  $K_{i'}$  (see Figure 1).

To each auxiliary function  $w_{\iota,k}$ , we associate the multiscale basis function  $\Psi_{\iota,k} = -k(x)\nabla w_{\iota,k}$ . When basis functions have been computed for each edge, we define the finite dimensional space for approximation of the velocity

$$V_h(k) = \bigoplus_{\iota} \{\Psi_{\iota,k}\},$$
  
 $V_h^0(k) = V_h(k) \cap H_0(\operatorname{div}, \Omega).$ 




Figure 1: Local problem to solve for multiscale basis.

Note that for each permeability field k, we associate a velocity approximation space  $V_h(k)$  that is spanned by the set of basis functions consisting of one multiscale basis function for each edge of every grid block in the coarse grid. In Section 3 we introduce to different approximation spaces for the velocity.

The choice of the boundary conditions  $g_{\iota}$  in (2.6) can affect the accuracy of MsFEM. In the following subsections we introduce two different kinds of boundary conditions, local and global boundary conditions where for global boundary conditions, we employ a single-phase flow velocity field.

## 2.2 Mixed MsFEM using local information

In [9], piecewise constant coarse-scale fluxes on the boundary of the coarse elements are used, i.e.,

$$g_{\iota} = \frac{1}{|\Gamma_{\iota}|}.$$

In this case, the boundary conditions do not contain any fine-scale information that is in the velocity field of the reference solution. In general, we also consider as a local approach any other boundary conditions that involve local information, e.g., permeabilities within the local domain.

## 2.3 Mixed MsFEM using limited global information

For accurate approximations of the fluxes, the velocity should contain fine-scale features similar to the solution. Approaches such as oversampling or limited global information [16, 12] are introduced for mixed finite element methods. The main idea of these techniques is to use larger regions for local problem computations, i.e., the local problems are solved in larger regions and then the basis functions are computed using only the interior information. In the following we use

$$g_{\iota} = \frac{v \cdot n_{ii'}}{\int_{\Gamma_{\iota}} v \cdot n_{ii'} ds},$$

with the 'global' velocity v which solves the single-phase flow equation (2.4).

Here, we note that global approaches are known to be more accurate for a given realization of the permeability field ([4]). However, they are computationally more expensive, since the boundary condition depends on the 'global' velocity v which requires to solve a global fine-scale problem.

## 3 Ensemble level methods for mixed MsFEM

The main idea of ensemble level multiscale methods is to construct local basis functions that can be used for any member of the ensemble. These calculations involve selecting some ensemble members and constructing multiscale basis functions for them. The computations are divided in offline and online computations. In this section we introduce two ensemble level methods for mixed MsFEM, the no-local-solve-online ensemble level method (NLSO) and the local-solve-online ensemble level method (NLSO). In both methods the offline part is to construct sets of basis functions based on a few  $(N_l)$  realizations of the solution. We choose these realizations randomly or use proper orthogonal decomposition (POD) to identify best local basis functions in the norm defined by POD for the velocity field. In general we can also choose offline realizations following the techniques used in reduced basis methods (cf.[21, 22]). For both methods we can use either boundary conditions using global single-phase flow information or local information.

The main idea of NLSO is to use all pre-computed basis functions to construct a coarse-grid approximation. This is done by projecting the solution onto the space of pre-computed basis functions. On the other hand, LSO computes a few (one in our case) multiscale basis functions per edge by projecting the local problem onto the space of pre-computed basis functions. The local problem typically requires some boundary conditions. For a given realization, we can only use local boundary conditions because the use of limited global information will involve solving a global single-phase flow equation. For this reason, as we will show that LSO is less accurate compared to NLSO when global information is used.

## 3.1 No-local-solve-online ensemble level method (NLSO)

The no-local-solve-online mixed MsFEM method was introduced in [3]. The main idea is to pre-compute multiscale basis functions on a coarse-grid block for a few randomly chosen realizations. These basis functions are further used to solve the global flow equation (2.4). In particular, at each interior edge  $\Gamma_{\iota}$  and for a few coefficients  $k_j(x) = k(x, \omega_j)$ ,  $1 \le j \le N_l$ , we define the multiscale basis functions  $\Psi_{\iota,k_j}(x) = -k_j(x)\nabla w_{\iota,k_j}$ . Whereas  $w_{\iota,k_j}$  denotes the solution of (2.6) with the coefficient  $k_j(x)$ .

These basis functions are used to solve the equation on a coarse grid for an arbitrary realization of the permeability without re-computing new basis functions. Following [3], we employ an approximation space for the velocity that is defined for multiple  $k_i$ , i.e., we use

$$V_h^{NLSO} = \bigoplus_{j=1}^{N_l} V_h(k_j).$$

The coarse space of all the pre-computed basis functions is used to solve the equation (2.4) on a coarse grid. This velocity we use to solve the transport equation (2.2) with an implicit scheme to determine the saturation.

Therefore we solve the equations on a  $N_l \times |\mathcal{I}|$  coarse space (since we have  $N_l$  basis functions on each edge instead of one).

Since the basis functions do not change during the online stage, we can pre-compute the integrals such as  $\int \Psi_{\iota,k_j} \Psi_{\iota',k_j'}$ .

To identify the best local basis we use proper orthogonal decomposition. Therefore we compute the  $\tilde{N}$  eigenvalues with the largest absolute value and the corresponding eigenvectors  $\tilde{V}_i = (\tilde{V}_i^1, \cdots, \tilde{V}_i^{N_l}), \ 1 \leq i \leq \tilde{N}$ , of the matrix  $B_\iota^T B_\iota$ . Here  $B_\iota$  denotes the matrix of pre-computed multiscale basis functions for an edge  $\iota$ , i.e., of  $B_\iota = (\Psi_{\iota,k_j})_{1 \leq j \leq N_l}$ . We denote with V the matrix of the scaled eigenvectors, i.e., for each column of the matrix it holds:  $V_i = \frac{1}{\sum_{j=1}^{N_l} \tilde{V}_j^i} \tilde{V}_i$ .

For POD multiscale basis functions we use the columns of  $\widetilde{B}=BV$ . We have implemented the POD approaches using the  $L^2$  inner product of the velocity. We observe an improvement of the approximation of the velocity and the saturation (cf. Section 5.3). For instance, we get a velocity error of 0.14% with POD and 0.09% without POD for an isotropic Gaussian distribution. For the saturation we have 2.02% with POD and 1.32% without POD. The gain in the POD approach is larger for the velocity since we consider the  $L^2$  inner product of the velocity. It is not clear if this inner product is optimal for the quantity of interest: the water saturation. The choice of an optimal inner product for the saturation will be investigated in future work. For MLMC convergence we have not observed any gain using the POD approach. (cf. Section 5.6).

## 3.2 Local-solve-online ensemble level method (LSO)

The local-solve-online ensemble level method is similar to a reduced basis approach (e.g., [11, 21]). However, in comparison to reduced basis methods where the realizations fulfill special properties, we select the realizations for the precomputations randomly. We apply the local-solve-online ensemble level method in the context of mixed multi-scale FEM as follows. The offline part coincided with the offline part of the above introduced NLSO method. We construct sets of basis functions based on a few  $(N_l)$  randomly chosen realizations of the coefficient  $k_j(x) = k(x, \omega_j)$ ,  $1 \le j \le N_l$  or we can use POD to select basis functions as described above.

After we have solved (2.6) for each realization we define for every edge  $\iota = \{ii'\}$  a space  $V_h^\iota := \bigoplus_{j=1}^{N_l} \Psi_{\iota,k_j}$ . In this space  $V_h^\iota$  we approximate in the online stage the solution  $\tilde{w}_{\iota,\tilde{k}}$  of the auxiliary problem (2.6) with some local

boundary conditions with the coefficient  $\tilde{k}(x) = k(x, \tilde{\omega})$  for a random  $\tilde{\omega}$ . As an approximation space for the velocity we define now

$$V_h^{LSO} = \bigoplus_{\iota \in \mathcal{I}} \{\tilde{\Psi}_{\iota,\tilde{k}}\},$$

for  $\tilde{\Psi}_{\iota,\tilde{k}} = -\tilde{k}(x)\nabla \tilde{w}_{\iota,\tilde{k}}$ . For each computed multiscale velocity we solve the transport equation (2.2) to compute the saturation.

In this approach we use a different multiscale basis for each coefficient. That is the reason why the integrals  $\int \tilde{\Psi}_{\iota,\tilde{k}} \tilde{\Psi}_{\iota',\tilde{k}}$  over a coarse block cannot be precomputed. However, since each basis function  $\tilde{\Psi}_{\iota,\tilde{k}}$  is a linear combination of the pre-computed basis functions  $\Psi_{\iota,k_j}$ ,  $1\leq j\leq N_l$ , the calculations can be done inexpensively using pre-computed quantities.

As in the previous approach NLSO we can use POD to find the best local basis. Again we observe an improvement in the numerical simulations for approximating the velocity and the saturation (cf. Section 5.3). Analogous to the NLSO method the use of POD does not change the results for MLMC and MC significantly.

#### 3.3 Comparison of LSO and NLSO

In contrast to the NLSO method, the online computations of the LSO method are divided into two parts, first one solves in each interior edge of the coarse region a local problem of size  $N_l^2$  to get a basis for a chosen realization. Once multiscale basis functions are identified for each edge, the global problem is solved on a coarse grid by projecting the solution. In the NLSO approach we solve the equations on a  $N_l$  times larger coarse space (since we have  $N_l$  basis functions on each edge instead of one) while the accuracy of the method is not sacrificed at the expense of a specific boundary condition.

If the boundary condition  $g_{\iota}$  in (2.6) uses the local information which does not depend on the permeability, the NLSO and the LSO approach have almost the same accuracy. In the NLSO case we approximate the velocity with

$$v = \sum_{\iota \in \mathcal{I}} \sum_{i=1}^{N_l} c_{\iota j} \Psi_{\iota, k_j}$$

and in the LSO approach with

$$v = \sum_{\iota \in \mathcal{I}} c_{\iota} \tilde{\Psi}_{\iota, \tilde{k}} = \sum_{\iota \in \mathcal{I}} c_{\iota} \sum_{j=1}^{N_{l}} c_{j} \Psi_{\iota, k_{j}}.$$

This is exactly the same if we have the freedom to choose  $c_i$ . Note that the coefficients  $c_i$  in LSO are determined from the solution of local problems that compute basis functions.




Figure 2: Comparison of LSO and NLSO.

Global information is important as it was demonstrated in [20, 12] theoretically and numerically. This is particularly true when the problem is solved multiple times. In this section, our goal is to show that when global information is used one cannot use LSO type approaches and need NLSO if an accurate solution is sought.

Since the cost of the online computation of the NLSO approach does not depend on the boundary condition  $g_t$  it is reasonable to choose limited global boundary conditions. The first part of the online computations of the LSO method is to solve the auxiliary problem (2.6). Boundary conditions using global information would increase the computational cost of the method. With this choice of boundary condition there would be no computationally gain of an ensemble level method compared to a standard mixed MsFEM method for each particular realization in our setup. Therefore we choose local boundary conditions for the online part of the LSO method (global for the offline part). With this choice of boundary conditions the computational cost for NLSO and LSO is comparable. The NLSO approach is more accurate than the LSO method if global boundary conditions are used as we will show in Section 5.3.

## 4 Multi-level Monte Carlo methods using ensemble level mixed MsFEM

First we introduce multi-level Monte Carlo in a general way and after that we combine it with the introduced ensemble level mixed MsFEMs, NLSO and LSO. Denote G a generic random function,  $G = G(x, \omega)$ . We are interested in the efficient computation of the expectation of G, denoted by E(G). The idea of multi-level Monte Carlo (MLMC) methods is to consider the quantity of interest at different levels l. We introduce levels smaller than L, such as L-1,...,1 where we assume that the computation at the smallest level is cheap, while less accurate, to compute and  $G_0 = 0$ . Particularly, we assume  $||G_l - G|| \sim \frac{1}{N_l^\beta}$ , with  $N_1 \leq N_2 \leq \cdots \leq N_L$  and  $\beta > 0$ .  $N_l$  is related to the accuracy of the approximation (see discussion below). As an approximation of the expectation E(G) we use the multi-level approximation

$$E^{L}(G_{L}) = \sum_{l=1}^{L} E_{M_{l}} (G_{l} - G_{l-1}), \qquad (4.1)$$

where  $E_{M_l}$  denotes the arithmetic mean with  $M_l$  samples. For error estimates, we consider the root mean square errors

$$||E(G_L) - E^L(G_L)|| := \left(E(||E(G_L) - E^L(G_L)||_B^2)\right)^{\frac{1}{2}}$$
(4.2)

with an appropriate norm  $\|\cdot\|_B$ . We get

$$||E(G_{L}) - E^{L}(G_{L})||$$

$$= ||E\left(\sum_{l=1}^{L} (G_{l} - G_{l-1})\right) - \sum_{l=1}^{L} E_{M_{l}} (G_{l} - G_{l-1})||$$

$$\leq \sum_{l=1}^{L} ||(E - E_{M_{l}})(G_{l} - G_{l-1})||$$

$$\leq \sum_{l=1}^{L} \frac{1}{\sqrt{M_{l}}} ||G_{l} - G_{l-1} - E(G_{l} - G_{l-1})||$$

$$\lesssim \sum_{l=1}^{L} \frac{1}{\sqrt{M_{l}}} ||G - G_{l}|| + \frac{1}{\sqrt{M_{1}}}$$

$$\lesssim \sum_{l=2}^{L} \frac{1}{\sqrt{M_{l}}} \frac{1}{N_{l}^{\beta}} + \frac{1}{\sqrt{M_{1}}}.$$

To equate the error terms we choose

$$M_{l} = C \begin{cases} N_{L}^{2\beta}, & l = 1\\ \left(\frac{N_{L}}{N_{l}}\right)^{2\beta}, & 2 \leq l \leq L, \end{cases}$$

$$(4.3)$$

then we end with

$$||E(G_L) - E^L(G_L)|| = O\left(\frac{1}{N_L^{\beta}}\right).$$
 (4.4)

We are interested in predicting of the saturation field and will measure the mean square error in the saturation field. We use both ensemble level mixed MsFEMs -NLSO and LSO- to calculate  $G_l$  where  $N_l$  realizations of the permeability field are chosen to compute the basis for the whole ensemble.

At each level l we select a different number of realizations of the permeability field  $N_l, N_1 \leq N_2 \leq \cdots \leq N_L$  to build a low dimensional approximation space for velocity that captures both small scale (sub coarse-grid) spatial variability in the permeability data and stochastic variability due to uncertainties in the data. In particular, we calculate the velocity at level l for  $M_l$  realizations to get saturations  $S_{l,m}$  with  $1 \leq l \leq L$  and  $1 \leq m \leq M_l$  to build the MLMC approximation of the expected value of the fine scale saturation. For clarity we summarize the basic steps below.

## 1. Generation of coarse grid.

• Partition the domain into a coarse grid. The coarse grid is a partitioning of the fine grid where each cell in the fine grid belongs to a unique block in the coarse grid and each coarse grid block is connected. [1].

- 2. Construction of multiscale approximation space  $V_h$ :
  - $\bullet$  Select  $N_L$  realizations from the stochastic permeability distribution.
  - For each selected realization  $1 \le j \le N_L$ :
    - Solve (2.4) on the fine grid using a suitable mass conservative numerical method to obtain a 'global' velocity solution  $v_j$ .
    - Compute the multiscale basis functions: For each edge  $\Gamma_{\iota}$ ,  $\iota = \{ii'\}$ , set

$$g_{\iota}(k_j) = rac{v_j \cdot n_{ii'}}{\int_{\Gamma_{\iota}} v_j \cdot n_{ii'} ds},$$

and solve (2.6) to obtain  $w_{\iota,k_i}$  and subsequently  $\Psi_{\iota,k_i}$ .

- Define  $V_h(k_i) = \bigoplus_{\iota} \Psi_{\iota,k_i}$ .
- 3. Multi-level mixed MsFEM computations for estimating an expectation at level l,  $1 \le l \le L$ :
  - Select  $M_l$  realizations of the permeability  $k_{m_l}$ ,  $1 \leq m_l \leq M_l$ .
  - LSO method:
    - Compute:  $\tilde{\Psi}_{\iota,k_{m_l}} \in V_h^{\iota} = \bigoplus_{j=1}^{N_l} \Psi_{\iota,k_j}$  by solving (2.6) with  $k_{m_l}$  and local B.C..
    - Define  $V_h^{LSO} = \bigoplus_{\iota} \{\tilde{\Psi}_{\iota,k_{m_{\iota}}}\}$
    - Solve two-phase flow and transport (2.1)-(2.2) for  $S_{l,m}$ . At each time step, the velocity field is constructed by solving (2.1) on a coarse grid using  $V_h^{LSO}$ .
  - NLSO method:
    - Define  $V_h^{NLSO} = \bigoplus_{j=1}^{N_l} V_h(k_j)$ .
    - Solve two-phase flow and transport (2.1)-(2.2) for  $S_{l,m}$ . At each time step, the velocity field is constructed by solving (2.1) on a coarse grid using  $V_h^{NLSO}$ .
  - Calculate the arithmetic mean

$$E_{M_l}(S_l - S_{l-1}) = \frac{1}{M_l} \sum_{m=1}^{M_l} (S_{l,m} - S_{l-1,m}).$$
 (4.5)

4. MLMC approximation of E(S)

$$E^{L}(S_{L}) = \sum_{l=1}^{L} E_{M_{l}}(S_{l} - S_{l-1}). \tag{4.6}$$

Next, we discuss the work for MLMC and compare it with MC. We will consider two cases: single-phase flow  $(\lambda(S) = 1 \text{ and } f(S) \text{ nonlinear})$  and two-phase flow. In both cases, we will compare the saturation field at a certain time instant. In all simulations, we will ignore the cost of pre-computations as

basis functions are fixed throughout the simulations. Note that we have almost the same numerical costs for NLSO and for LSO, if we assume we solve the pressure equation optimally. The computational cost for solving the pressure equation each time instant with  $N_l$  basis functions (at level l) for a coarse grid  $H_j$  is  $2(H_j^{-1}-1)N_l^2H_j^{-1}$ . For LSO we solve at each interior edge an  $N_l^2$  problem and solve the pressure equation for only one set of basis functions we get  $2(H_j^{-1}-1)(N_l^2+1)H_j^{-1}$ . In the following we neglect the costs of solving the pressure equation for one set of basis functions in LSO, such that we end with the same numerical costs for NLSO and LSO. But of course it is possible to calculate the online multiscale LSO basis of each edge in parallel, such that the computational time for LSO is much smaller. In our simulations, we will equate the cost of solving the pressure equation for MC and MLMC and compare the accuracy of these approximations. Although for single-phase flow this comparison is accurate (up to the cost of computation of basis functions), one needs to take into account the cost of solving the saturation equation in two-phase flow and transport simulations. The cost of the computation for the saturation equation at each time instant is the same at any level because we use a coarse-grid velocity field. We note the cost of solving the pressure equation is larger than that for the saturation equation on a coarse grid because the convergence of iterative solvers requires many iterations for multiscale problems and there are more degrees of freedom. Since we use several basis functions per coarse edge in the ensemble level multiscale method, the cost computing the pressure solution can be several times larger than that of the saturation equation because the coarse system is several times larger for the pressure equation. We will ignore the cost of saturation computation on a coarse grid in two-phase flow examples.

We have the following computational costs for MLMC based on pressure:

$$W_{MLMC}$$

$$= \sum_{l=1}^{L} \left( 2 \left( H_j^{-1} - 1 \right) N_l^2 H_j^{-1} \right) M_l$$

$$= 2N_L^{2\beta} H_j^{-1} (H_j^{-1} - 1) \left( \sum_{l=2}^{L} N_l^{2-2\beta} + N_1^2 \right).$$

We compare the costs with the computational costs for MC

$$W_{MC} = \left(2(H_j^{-1} - 1)\widehat{N}^2 H_j^{-1}\right)\widehat{M}.$$
 (4.7)

In our numerical simulations, we will equate the work and compare the accuracy of MLMC and MC. When comparing the work, we will calculate the number of realizations for detailed two-phase flow and transport simulations that are needed.

We have observed that the accuracy of ensemble level multiscale methods increases as we increase the dimension of the coarse space (see [3] and the discussions below). However, this accuracy can not be estimated, in general.

We propose the use of an empirical procedure that allows, based on simulations with a few samples, to estimate the convergence rate of ensemble level mixed MsFEM; further, using these estimates we select the number of realizations,  $M_i$  (see (4.3)) in MLMC.

## 5 Numerical results

In our numerical examples, we will consider permeability fields described by two-point correlation functions. We will use the Karhunen-Loève expansion (KLE) to parameterize these permeability fields and apply the MLMC algorithm as described above. We will compute the number of MC realizations needed to achieve the same amount of work and compare the accuracy of MLMC and MC. First, we briefly describe the permeability parameterization and then we will present numerical results.

## 5.1 Permeability parameterization

To obtain the permeability field in terms of an optimal  $L^2$  basis, we use the Karhunen-Loève expansion (KLE) [19]. For our numerical tests, we truncate the expansion and represent the permeability matrix by a small number of random parameters. We briefly recall the facts of the KLE. Consider  $Y(x,\omega) = \log[k(x,\omega)]$ , where  $\omega$  represents randomness. We assume that  $E[Y(x,\omega)] = 0$  and R(x,y) = E[Y(x)Y(y)]. We will expand  $Y(x,\omega)$  as

$$Y(x,\omega) = \sum_{k=1}^{\infty} Y_k(\omega)\psi_k(x),$$
  $Y_k(\omega) = \int_{\Omega} Y(x,\omega)\psi_k(x)dx,$ 

where  $\psi_k(x)$  is an orthonormal basis that are eigenvectors of R(x,y) when discretized. More precisely,  $\{\psi_k\}$  is a complete basis in  $L^2(\Omega)$ . It follows that  $\psi_k(x)$  are eigenfunctions of R(x,y):

$$\int_{\Omega} R(x,y)\psi_k(y)dy = \lambda_k \psi_k(x), \qquad k = 1, 2, \dots,$$
(5.1)

where  $\lambda_k = E[Y_k^2] > 0$ . Note that  $E(Y_iY_j) = 0$  for all  $i \neq j$ . Denoting  $\eta_k = Y_k/\sqrt{\lambda_k}$   $(E(\eta_k) = 0$  and  $E(\eta_i\eta_j) = \delta_{ij})$ , we have

$$Y(x,\omega) = \sum_{k=1}^{\infty} \sqrt{\lambda_k} \eta_k(\omega) \psi_k(x), \qquad (5.2)$$

where  $\psi_k$  and  $\lambda_k$  satisfy (5.1). The randomness is represented by the scalar random variables  $\eta_k$ . After the discretization of the domain  $\Omega$  in a rectangular mesh, we truncate the KLE (5.2) to finite terms. We only keep the leading order terms (quantified by the magnitude of  $\lambda_k$ ) and capture most of the energy of the stochastic process  $Y(x,\omega)$ . For an N-term KLE approximation  $Y_N = \sum_{k=1}^N \sqrt{\lambda_k} \eta_k \psi_k$ , the energy ratio of the approximation is defined as e(N) :=

 $\frac{E\|Y_N\|^2}{E\|Y\|^2} = \frac{\sum_{k=1}^N \lambda_k}{\sum_{k=1}^\infty \lambda_k}$ . If  $\lambda_k, k = 1, 2, \dots$ , decay very fast, then the truncated KLE would be a good approximation of the stochastic process in the  $L^2$  sense.

We will consider two types of correlation functions. The first one is log-Gaussian

$$R(x,y) = \sigma^2 \exp\left(-\frac{|x_1 - y_1|^2}{2l_1^2} - \frac{|x_2 - y_2|^2}{2l_2^2}\right),\tag{5.3}$$

and the next one is log-Exponential

$$R(x,y) = \sigma^2 \exp\left(-\frac{|x_1 - y_1|}{l_1} - \frac{|x_2 - y_2|}{l_2}\right).$$
 (5.4)

In the above formula,  $l_1$  and  $l_2$  are the correlation lengths in each dimension, and  $\sigma^2 = E(Y^2)$  is a constant that represents the variance of the permeability field. In the first case, we expect faster decay of eigenvalues compared to the second case, log-Exponential, for a given set of correlation lengths.

## 5.2 Experimental setup

In our simulations we consider the traditional quarter-of-a-five-spot with no-flow boundary conditions. The domain  $\Omega$  is a square and we inject water at the upper left corner while the producer is placed at the lower right one. The pressure equation (2.1) is solved with mixed MsFEM and we solve for the saturation with an implicit scheme. In the numerics we solve (2.1) on a coarse grid or on a fine grid. If we solve on the fine grid, we take the transport equation with the right-hand side zero. On the fine grid we solve a single-phase flow problem and on the coarse grid a two-phase flow problem. In both cases the permeability field Y(x) is given on a  $100 \times 100$  fine Cartesian grid. As mentioned above, we consider Gaussian and Exponential covariance functions. In all examples we have  $\sigma^2 = 2$ . In particular we consider:

- Isotropic Gaussian field: correlation length  $l_1 = l_2 = 0.2$ , stochastic dimension 10
- Anisotropic Gaussian field: correlation length  $l_1=0.5$  and  $l_2=0.1$ , stochastic dimension 12
- Isotropic Exponential field: correlation length  $l_1 = l_2 = 0.2$ , stochastic dimension 300
- Anisotropic Exponential field: correlation length  $l_1 = 0.5$  and  $l_2 = 0.1$ , stochastic dimension 350

To build the multiscale basis, we generate  $N_L$  independent realizations of the permeability.

We have also selected a POD basis as described in Section 3. But we have not observed any gain for MLMC. For this reason we mostly show the results for randomly chosen realization for the offline stage. We briefly show some results using the POD approach to pre-compute the multiscale basis for two-phase flow.

The multiscale basis functions are not recomputed during the simulations, i.e., they are computed at time zero. We compare the MLMC accuracy of the saturation at a certain time instance (PVI= 0.8) with the accuracy of standard MC at level L with the same amount of costs; therefore, we choose

$$\widehat{M} = \frac{\sum_{l=1}^{L} N_l^2 M_l}{N_l^2}.$$
(5.5)

As reference, we use the arithmetic mean of  $M_{ref}$  samples of the saturation solved with the multiscale velocity where the basis is calculated for the permeability realization which is used in the pressure equation. We denote the reference saturation with  $S_{ref}$ . We consider the square root of the arithmetic mean of square of the relative  $L^2$  errors, e.g., for MLMC we consider

MLMC error = 
$$\sqrt{\frac{1}{J} \sum_{j=1}^{J} \frac{\|S_{ref} - S_{MLMC}^{j}\|_{L^{2}}^{2}}{\|S_{ref}\|_{L^{2}}^{2}}}$$
, (5.6)

where  $S_{MLMC}^{j}$  denotes the MLMC approximation of the expectation for a given set of permeability realization  $\{k_1, \dots, k_{N_L}\}$  to compute the multiscale basis functions (cf. (2.6)) and different realizations  $\{k_1, \dots, k_{m_1}\}$  to solve the flow an transport equations (cf. (2.1)-(2.2)) to compute the saturation.

## 5.3 Comparison of the NLSO and LSO approach for single-phase flow

In this section we briefly study the differences of the two ensemble level mixed MsFEM and the influence of the choice of different boundary conditions using local or limited global information for single-phase flow.

We show that methods using local boundary conditions have a residual error no matter how many basis functions we pick.

Therefor we pre-compute 12 basis functions with either local or global boundary conditions. We study the influence based on an isotropic Gaussian and an anisotropic Exponential distribution. For the selected realization  $k_j$  we consider the L<sup>2</sup>-error between the water saturation computed with one of the ensemble level methods with either local or global boundary conditions and a reference saturation. As reference we use either the fine-scale water saturation,  $S_{ref}^{j}$ , or the multiscale saturation,  $S_{refloc}^{j}$ , where the basis is calculated for the realization  $k_j$  with local boundary conditions. In our case the local boundary conditions are a combination of the permeability in different cells. Note, that the goal is not to compare local and global boundary conditions but the goal is to compare the NLSO and LSO approaches. We show that the LSO method does not remove the residual error. In Table 1 we computed the mean L<sup>2</sup>-errors of 100 different realizations for all the combinations. Again, note that we solve the online problem for LSO with local boundary conditions. The mean error between the reference saturation with local and global boundary conditions is

	isotropic Gaussian			aniso	tropic l	Exponen	tial	
ll a all	gNLSO	gLSO			gNLSO	0		
$  S_{ref} - S  $ $  S_{reflec} - S  $	0.33 $16.21$	16.06 $1.88$	1.91 $16.02$	16.16 $0.75$	16.18 30.18	33.60 $19.88$	21.47 $27.19$	34.00 $17.59$

Table 1: Mean errors (percent) of 100 realizations for the different methods and boundary conditions for the single-phase flow example.

approximately 16% for the Gaussian and 34% for the Exponential distribution. It is known from literature (cf. [4]) that the source of the errors are the local boundary conditions and boundary conditions using global information should be used to overcome this problem.

From the table we see that in the LSO method we introduce an additional error by solving the online problem with local boundary conditions. The NLSO seems to be a good approximation of the fine-scale saturation, while the solution of LSO is closer to the local reference. For instance, we have an error of less than 1% for the NLSO with global boundary conditions for the Gaussian distribution. The error of the LSO approach to the global reference is of the same size as the error between the global reference and the local one independent of the underlying distribution. In both approaches global boundary conditions give the better approximation of the fine-scale saturation. For this reason we will consider only global boundary conditions in the following. In Figure 3 we show the water saturations with global boundary conditions for one sample of the isotropic Gaussian and the anisotropic Exponential random field.




Figure 3: Water saturation for global boundary condition for the different methods.

## 5.4 Convergence rate

In Section 4 we assume  $||G_l - G|| = C \frac{1}{N_l^{\beta}} =: \delta_l$ , with  $\delta_1 > \delta_2 > \cdots \delta_L$ . In this section we investigate  $\delta_l$  where G denotes the saturation with the basis calculated for the permeability realization which is used in the pressure equation and  $G_l$  the saturation with a pre-computed basis for  $N_l$  permeability realizations. With these  $\delta_l$ s, it is possible to find appropriate choices of realizations  $M_l$  at each level, namely

$$M_{l} = C \begin{cases} \left(\frac{1}{\delta_{L}}\right)^{2} (\operatorname{std}(G) + \delta_{1}^{2}), & l = 1\\ \left(\frac{\delta_{l}}{\delta_{L}}\right)^{2}, & 2 \leq l \leq L. \end{cases}$$

In the previous section we observed that the LSO approach does not converge to the fine scale saturation. For this reason we consider the NLSO case only. Furthermore, we observe similar convergence rates if we choose the realization for the pre-computations randomly or if we use the POD approach. So we present the results for the random selection case. For further studies we refer to [17].

To determine the convergence rate, we choose  $\mathcal{N}=(3,6,12)$  and calculate the mean over M=100 permeability realizations as follows. For 10 sets of permeability realizations we compute the multiscale basis and each of these sets we use to compute the error for 10 different permeability realizations. We compute the arithmetic mean of the  $10\times 10$  numbers. The resulting  $\delta$ s depend on the underlying distribution of the covariance function, but at least in the two-phase flow example the ratio  $\frac{\delta_l}{\delta_L}$  remains almost the same for all distributions. For the Gaussian distributions (isotropic and anisotropic) we get approximately (2.7,1.6,1) and for the Exponential ones (2.0,1.5,1). In the single-flow case the ratio is the same for the isotropic and anisotropic Exponential distribution we get for the ratios (1.6,1.3,1). If the covariance is Gaussian, the decay is much faster than in the Exponential case and the decay is even much faster for the isotropic Gaussian distribution. The ratios in the isotropic Gaussian case are (13.6,5.1,1) and in the anisotropic Gaussian (5.2,2.6,1).

## 5.5 Single-phase flow

As mentioned above, we denote the example as single-phase flow, if the total mobility  $\lambda(S) = 1$ . We take the flux term  $f(S) = \frac{S^2}{S^2 + (1-S)^2}$  (see (2.2)). Since the mobility does not depend on the saturation, we solve (2.1) only once and update the transport equation for each time step.

The parameters we use for our simulation and the resulting relative errors for the different distributions are summarized in Table 2. In Figure 4 we have plotted the water saturation for the different covariance functions (isotropic and anisotropic Gaussian, isotropic and anisotropic Exponential) and the different methods (MLMC and MC) in the case of NLSO. In Figure 5 we used LSO. We choose the numbers of samples at each level as  $\mathfrak{M} = (70, 20, 10)$  and the

	isotropic Gaussian	anisotropic Gaussian	isotropic Exponential	anisotropic Exponential
$(N_1, N_2, N_3)$	(3, 6, 12)	(3, 6, 12)	(24, 48, 96)	(24, 48, 96)
$(M_1, M_2, M_3)$	(70, 20, 10)	(70, 20, 10)	(70, 20, 10)	(70, 20, 10)
$\widehat{N}$	12	12	96	96
$\widehat{M}$	20	20	20	20
$M_{MCref}$	500	500	500	500
MLMC error NLSO	0.0758	0.0847	0.0934	0.0889
MC error NLSO	0.1439	0.1222	0.1389	0.1343
MC error NLSO	1.90	1.44	1.49	1.51
MLMC error LSO	0.1101	0.1189	0.1781	0.1711
MC error LSO	0.3027	0.4244	0.2112	0.1839
MC error LSO	2.75	3.57	1.19	1.07

Table 2: Parameters and errors for the single-phase flow example.

dimension of the approximation space (defined as number of independent samples selected to construct the multiscale space) for the Exponential distributions eight times larger than for the Gaussian tests. We equate the computational costs and compare the resulting relative errors for MLMC and MC. With this choice of realizations for MLMC, we get for MC with equated costs  $\widehat{M}=20$ , where  $\widehat{M}$  is the number of permeability realizations needed for forward simulations. We repeat these calculation for 20 sets of multiscale basis function, i.e., J=20 in (5.6).

In the NLSO case we get for MLMC relative errors of approximately 9 percent and for MC approximately 13 percent. This result is almost independent of the underlying distribution, but note that for the Exponential test cases the computational work is eight times larger than for the Gaussian ones. So the MC error is 1.5 times larger than the MLMC one. In the LSO case we introduce an additional error by projecting the multiscale basis onto the space of the  $N_l$  pre-computed basis functions due to the local boundary conditions. So both errors are larger, but the MC error is about 3 times larger than the MLMC one.

We observe similar results if the POD approach is used. So we show the results for the random case. We will only show some results for the POD case in the two-phase flow example (cf. Section 5.6).

Again we note that one could do the computations of the multiscale basis of the LSO method in parallel and so it is possible to decrease the errors by keeping the computational time fixed.

## 5.6 Two-phase flow

We consider a  $5 \times 5$  coarse grid, such that every grid block contains a  $20 \times 20$  cell partition from the fine grid. We choose  $\mu_w = 1$ ,  $\mu_0 = 1$ ,  $k_{rw}(S) = S^2$  and  $k_{ro}(S) = (1-S)^2$ . We solve the pressure equation on the  $5 \times 5$  coarse grid with mixed MsFEM for each time step. The parameters we use for our simulation and the resulting relative errors for the different covariance functions (isotropic and anisotropic Gaussian, isotropic and anisotropic Exponential) are summarized in Table 3. In Figure 6 we have plotted the water saturation for the different distributions and the different methods (MLMC and MC) in the case of NLSO and in Figure 7 we used LSO In all tests we use the same number of realizations




Figure 4: Water saturation for the different methods and distributions for single-phase flow using NLSO  $\,$ 




Figure 5: Water saturation for the different methods and distributions for single-phase flow using LSO.

	isotropic Gaussian	anisotropic Gaussian	isotropic Exponential	anisotropic Exponential
$(N_1, N_2, N_3)$	(3, 6, 12)	(3, 6, 12)	(24, 48, 96)	(24, 48, 96)
$(M_1, M_2, M_3)$	(70, 20, 10)	(70, 20, 10)	(70, 20, 10)	(70, 20, 10)
$\widehat{N}$	12	12	96	96
$\widehat{M}$	20	20	20	20
$M_{MCref}$	500	500	500	500
MLMC error NLSO	0.0522	0.0497	0.0529	0.0543
MC error NLSO	0.0989	0.0849	0.0947	0.0898
MC error NLSO	1.90	1.71	1.79	1.65
MLMC error LSO	0.0448	0.0854	0.0581	0.1161
MC error LSO	0.0839	0.1056	0.1039	0.1274
MC error MLMC error LSO	1.72	1.24	1.79	1.10
MLMC error POD NLSO	0.0479	0.0563	0.0568	0.0583
MC error POD NLSO	0.0884	0.0937	0.0972	0.0911
MC error MLMC error LSO	1.85	1.67	1.71	1.56
MLMC error POD LSO	0.0565	0.0843	0.0652	0.1299
MC error POD LSO	0.0992	0.1083	0.0952	0.1524
MC error MLMC error LSO	1.76	1.29	1.46	1.17

Table 3: Parameters and errors for the two-phase flow example.

for MLMC and following the same number of realizations for MC with equated costs. Namely  $\mathfrak{M}=(70,20,10)$  and  $\widehat{M}=20$ . But the number of basis functions differs for the Gaussian and Exponential cases. For the Exponential test, the dimension of each level is eight times larger than for the Gaussian. This means we increase the costs by eight. As in the single-phase example we choose J=20 in (5.6).

If we use NLSO the MC error is approximately 1.75 times larger than the MLMC error. Note that the gain is slightly larger for the isotropic distributions than for the anisotropic ones. For all distributions we end with a relative MLMC error of approximately 5 and a MC error of 9 percent. For LSO the errors are comparable. However, in this example we find that the gain is larger for isotropic distributions in comparison to the anisotropic ones. In the isotropic cases the MC error is about 1.75 times larger and for the anisotropic ones 1.2 times larger. Independent of the method -NLSO or LSO- we expect the ratio to increase if more levels are used.

Next we briefly mention POD results and show the convergence rate does not improve. As you can see in Table 3 some of the errors decrease, e.g., for NLSO with Gaussian distribution, and some increase, e.g., NLSO with anisotropic Gaussian. For NLSO the ratio of the MC and the MLMC error decreases slightly if we use POD for the offline computations of the basis functions. For LSO in most cases these ratios increase. However, since there is no clear trend for the errors, we see no gain in using the POD approach for MLMC.

## 6 Conclusions

In this paper, we combine multiscale finite element methods -NLSO and LSOand multi-level Monte Carlo (MLMC) techniques to speed-up Monte Carlo simulations. The multiscale methods solve the flow equation on a coarse grid with pre-computed basis functions using a few members of the ensemble. These basis functions are used to approximate the solution on a coarse grid for an arbitrary




Figure 6: Water saturation for the different methods and distributions for two-phase flow using NSLO.




Figure 7: Water saturation for the different methods and distributions for two-phase flow using LSO.

realization. The use of larger dimensional coarse spaces yields more accurate solutions. In multi-level Monte Carlo methods ([14, 13]) more accurate (and expensive) forward simulations are run with a fewer samples while less accurate (and inexpensive) forward simulations are run with a larger number of samples. Selecting the number of expensive and inexpensive simulations carefully, one can show that MLMC can provide a better accuracy at the same cost as MC. In our simulations, we use various dimensional coarse spaces and perform a number of forward simulations at different resolutions. These simulations results are further used within the MLMC framework to speed-up MC calculations. We present basic aspects of the algorithm and numerical results for coupled flow and transport in heterogeneous porous media.

## 7 Acknowledgment

This work was partially support by the DFG project. The implementation of the mixed MsFEM is based on the code of Aarnes. For further details we refer to [5, 18].

## References

- [1] J. E. Aarnes, S. Krogstad, and K. A. Lie. A hierarchical multiscale method for two-phase flow based upon mixed finite elements and nonuniform coarse grids. *Multiscale Model. Simul.*, 5(2):337–363, 2006.
- [2] J.E. Aarnes. On the use of a mixed multiscale finite element method for greater flexibility and increased speed or improved accuracy in reservoir simulation. SIAM MMS, 2:421–439, 2004.
- [3] J.E. Aarnes and Y. Efendiev. Mixed multiscale finite element methods for stochastic porous media flows. SIAM J. Sci. Comput., 30(5):2319–2339, 2008.
- [4] J.E. Aarnes, Y. Efendiev, and L. Jiang. Analysis of multiscale finite element methods using global information for two-phase flow simulations. SIAM MMS, 7(2):655–676, 2007.
- [5] J.E. Aarnes, T. Gimse, and K. A. Lie. An introduction to the numerics of flow in porous media using matlab. In *Geometric Modelling, Numerical Simulation*, and *Optimization*, pages 265–306. 2007.
- [6] A. Barth, C. Schwab, and N. Zollinger. Multi-Level Monte Carlo Finite Element method for elliptic PDE's with stochastic coefficients. Technical Report 2010-18, ETH Zürich, June 2010.
- [7] Y. Chen and L. Durlofsky. Ensemble level upscaling for efficient estimation of fine-scale production statistics. *SPE Journal*, (13):400–411, 2008.

- [8] Y. Chen, L. Durlofsky, M. Gerritsen, and X. Wen. A coupled local-global upscaling approach for simulating flow in highly heterogeneous formations. *Advances in Water Resources*, 26:1041–1060, 2003.
- [9] Z. Chen and T. Y. Hou. A mixed multiscale finite element method for elliptic problems with oscillating coefficients. *Math. Comput.*, 72(242):541–576, 2003.
- [10] K.A. Cliffe, M. Giles, R. Scheichl, and A. Teckentrup. Multilevel Monte Carlo methods and applications to elliptic PDEs with random coefficients. Preprint 1/11, 2011.
- [11] Y. Efendiev, J. Galvis, and F. Thomines. A systematic coarse-scale model reduction technique for parameter-dependent flows in highly heterogeneous media and its applications. *Multiscale Model. Sim.*, (submitted), 2011.
- [12] Y. Efendiev and T. Y. Hou. Multiscale finite element methods. Theory and applications. Springer, 2009.
- [13] M. Giles. Improved multilevel Monte Carlo convergence using the Milstein scheme. Keller, Alexander (ed.) et al., Monte Carlo and quasi-Monte Carlo methods 2006. Selected papers based on the presentations at the 7th international conference 'Monte Carlo and quasi-Monte Carlo methods in scientific computing', Ulm, Germany, August 14–18, 2006. Berlin: Springer. 343-358 (2008)., 2008.
- [14] M. Giles. Multilevel Monte Carlo path simulation. Oper. Res., 56(3):607–617, 2008.
- [15] S. Heinrich. Multilevel Monte Carlo methods. In S. Margenov, J. Wasniewski, and P. Yalamov, editors, Large-scale scientific computing. 3rd international conference, LSSC 2001, Sozopol, Bulgaria, June 6–10, 2001. Revised papers, volume 2179 of Lecture Notes in Computer Science, pages 58–67. Berlin: Springer, 2001.
- [16] T. Y. Hou and X. H. Wu. A multiscale finite element method for elliptic problems in composite materials and porous media. *J. Comput. Phys.*, 134(1):169–189, 1997.
- [17] C. Kronsbein. On some efficient numerical methods for multiscale problems with stochastic coefficients. PhD thesis, TU Kaiserslautern, 2012. In preparation.
- [18] K. A. Lie, S. Krogstad, I. Ligaarden, J. Natvig, H. Nilsen, and B. Skaflestad. Open-source MATLAB implementation of consistent discretisations on complex grids. *Comput. Geosci.*, 16(2):297–322, 2012.
- [19] M. Loeve. *Probability theory II.* 4th ed. Graduate Texts in Mathematics. 46. New York Heidelberg Berlin: Springer-Verlag. XVI, 413 p. , 1978.

- [20] H. Owhadi and L. Zhang. Metric-based upscaling. Communications on Pure and Applied Mathematics, 60(5):675–723, 2007.
- [21] A.T. Patera and G. Rozza. Reduced Basis Approximation and A Posteriori Error Estimation for Parameterized Partial Differential Equations, volume 1.0. to appear in (tentative rubric) MIT Pappalardo Graduate Monographs in Mechanical Engineering, 2006.
- [22] D.V. Rovas, L. Machiels, and Y. Maday. Reduced-basis output bound methods for parabolic problems. *IMA J. Numer. Anal.*, 26(3):423–445, 2006.

## Published reports of the Fraunhofer ITWM

The PDF-files of the following reports are available under:

## www.itwm.fraunhofer.de/de/ zentral berichte/berichte

D. Hietel, K. Steiner, J. Struckmeier A Finite - Volume Particle Method for Compressible Flows (19 pages, 1998)

2. M. Feldmann, S. Seibold

## Damage Diagnosis of Rotors: Application of Hilbert Transform and Multi-Hypothesis Testing

Keywords: Hilbert transform, damage diagnosis, Kalman filtering, non-linear dynamics (23 pages, 1998)

Y. Ben-Haim, S. Seibold

## Robust Reliability of Diagnostic Multi-Hypothesis Algorithms: Application to Rotating Machinery

Keywords: Robust reliability, convex models, Kalman filtering, multi-hypothesis diagnosis, rotating machinery, crack diagnosis (24 pages, 1998)

4. F.-Th. Lentes, N. Siedow

## Three-dimensional Radiative Heat Transfer in Glass Cooling Processes

(23 pages, 1998)

5. A. Klar, R. Wegener

### A hierarchy of models for multilane vehicular traffic

Part I: Modeling

(23 pages, 1998)

Part II: Numerical and stochastic investigations (17 pages, 1998)

6. A. Klar, N. Siedow

**Boundary Layers and Domain Decomposi**tion for Radiative Heat Transfer and Diffusion Equations: Applications to Glass Manufacturing Processes

(24 pages, 1998)

7. I. Choquet

Heterogeneous catalysis modelling and numerical simulation in rarified gas flows Part I: Coverage locally at equilibrium (24 pages, 1998)

8. J. Ohser, B. Steinbach, C. Lang Efficient Texture Analysis of Binary Images (17 pages, 1998)

9. J. Orlik

Homogenization for viscoelasticity of the integral type with aging and shrinkage (20 pages, 1998)

10. J. Mohring

Helmholtz Resonators with Large Aperture (21 pages, 1998)

11. H. W. Hamacher, A. Schöbel On Center Cycles in Grid Graphs (15 pages, 1998)

12. H. W. Hamacher, K.-H. Küfer Inverse radiation therapy planning a multiple objective optimisation approach (14 pages, 1999)

13. C. Lang, J. Ohser, R. Hilfer On the Analysis of Spatial Binary Images (20 pages, 1999)

14. M. Junk

On the Construction of Discrete Equilibrium **Distributions for Kinetic Schemes** 

(24 pages, 1999)

15. M. Junk, S. V. Raghurame Rao

A new discrete velocity method for Navier-Stokes equations

(20 pages, 1999)

16. H. Neunzert

Mathematics as a Key to Key Technologies (39 pages, 1999)

17. J. Ohser, K. Sandau

## Considerations about the Estimation of the Size Distribution in Wicksell's Corpuscle Problem

(18 pages, 1999)

18. E. Carrizosa, H. W. Hamacher, R. Klein, S. Nickel

## Solving nonconvex planar location problems by finite dominating sets

Keywords: Continuous Location, Polyhedral Gauges, Finite Dominating Sets, Approximation, Sandwich Algorithm. Greedy Algorithm (19 pages, 2000)

19. A. Becker

## A Review on Image Distortion Measures

Keywords: Distortion measure, human visual system (26 pages, 2000)

20. H. W. Hamacher, M. Labbé, S. Nickel, T. Sonneborn

## Polyhedral Properties of the Uncapacitated Multiple Allocation Hub Location Problem

Keywords: integer programming, hub location, facility location, valid inequalities, facets, branch and cut (21 pages, 2000)

21. H. W. Hamacher, A. Schöbel

## Design of Zone Tariff Systems in Public Transportation

(30 pages, 2001)

22. D. Hietel, M. Junk, R. Keck, D. Teleaga The Finite-Volume-Particle Method for Conservation Laws

(16 pages, 2001)

23. T. Bender, H. Hennes, J. Kalcsics, M. T. Melo, S. Nickel

## Location Software and Interface with GIS and Supply Chain Management

Keywords: facility location, software development, geographical information systems, supply chain management (48 pages, 2001)

24. H. W. Hamacher, S. A. Tjandra

Mathematical Modelling of Evacuation Problems: A State of Art

(44 pages, 2001)

25. J. Kuhnert, S. Tiwari

## Grid free method for solving the Poisson equation

Keywords: Poisson equation, Least squares method, Grid free method (19 pages, 2001)

26. T. Götz, H. Rave, D. Reinel-Bitzer, K. Steiner, H. Tiemeier

Simulation of the fiber spinning process Keywords: Melt spinning, fiber model, Lattice Boltzmann, CFD (19 pages, 2001)

27. A. Zemitis

On interaction of a liquid film with an obstacle Keywords: impinging jets, liquid film, models, numerical solution, shape (22 pages, 2001)

28. I. Ginzburg, K. Steiner

## Free surface lattice-Boltzmann method to model the filling of expanding cavities by Bingham Fluids

Keywords: Generalized LBE, free-surface phenomena, interface boundary conditions, filling processes, Bingham viscoplastic model, regularized models (22 pages, 2001)

29. H. Neunzert

»Denn nichts ist für den Menschen als Menschen etwas wert, was er nicht mit Leidenschaft tun kanne

Vortrag anlässlich der Verleihung des Akademiepreises des Landes Rheinland-Pfalz am 21.11.2001

Keywords: Lehre, Forschung, angewandte Mathematik, Mehrskalenanalyse, Strömungsmechanik (18 pages, 2001)

30. J. Kuhnert, S. Tiwari

## Finite pointset method based on the projection method for simulations of the incompressible Navier-Stokes equations

Keywords: Incompressible Navier-Stokes equations, Meshfree method, Projection method, Particle scheme, Least squares approximation AMS subject classification: 76D05, 76M28 (25 pages, 2001)

31. R. Korn, M. Krekel

## Optimal Portfolios with Fixed Consumption or Income Streams

Keywords: Portfolio optimisation, stochastic control, HJB equation, discretisation of control problems (23 pages, 2002)

32. M. Krekel

## Optimal portfolios with a loan dependent credit spread

Keywords: Portfolio optimisation, stochastic control, HJB equation, credit spread, log utility, power utility, non-linear wealth dynamics (25 pages, 2002)

33. J. Ohser, W. Nagel, K. Schladitz

## The Euler number of discretized sets - on the choice of adjacency in homogeneous lattices

Keywords: image analysis, Euler number, neighborhod relationships, cuboidal lattice (32 pages, 2002)

### 34. I. Ginzburg, K. Steiner

## Lattice Boltzmann Model for Free-Surface flow and Its Application to Filling Process in Casting

Keywords: Lattice Boltzmann models; free-surface phenomena; interface boundary conditions; filling processes; injection molding; volume of fluid method; interface boundary conditions; advection-schemes; upwind-schemes (54 pages, 2002)

35. M. Günther, A. Klar, T. Materne, R. Wegener

## Multivalued fundamental diagrams and stop and go waves for continuum traffic equations

Keywords: traffic flow, macroscopic equations, kinetic derivation, multivalued fundamental diagram, stop and go waves, phase transitions (25 pages, 2002)

## 36. S. Feldmann, P. Lang, D. Prätzel-Wolters Parameter influence on the zeros of network determinants

Keywords: Networks, Equicofactor matrix polynomials, Realization theory, Matrix perturbation theory (30 pages, 2002)

### 37. K. Koch, J. Ohser, K. Schladitz

# Spectral theory for random closed sets and estimating the covariance via frequency space

Keywords: Random set, Bartlett spectrum, fast Fourier transform, power spectrum (28 pages, 2002)

## 38. D. d'Humières, I. Ginzburg

## Multi-reflection boundary conditions for lattice Boltzmann models

Keywords: lattice Boltzmann equation, boudary condistions, bounce-back rule, Navier-Stokes equation (72 pages, 2002)

### 39. R. Korn

## Elementare Finanzmathematik

Keywords: Finanzmathematik, Aktien, Optionen, Portfolio-Optimierung, Börse, Lehrerweiterbildung, Mathematikunterricht (98 pages, 2002)

### 40. J. Kallrath, M. C. Müller, S. Nickel

## Batch Presorting Problems: Models and Complexity Results

Keywords: Complexity theory, Integer programming, Assigment, Logistics (19 pages, 2002)

### 41. J. Linn

## On the frame-invariant description of the phase space of the Folgar-Tucker equation

Key words: fiber orientation, Folgar-Tucker equation, injection molding (5 pages, 2003)

### 42. T. Hanne, S. Nickel

## A Multi-Objective Evolutionary Algorithm for Scheduling and Inspection Planning in Software Development Projects

Key words: multiple objective programming, project management and scheduling, software development, evolutionary algorithms, efficient set (29 pages, 2003)

43. T. Bortfeld , K.-H. Küfer, M. Monz, A. Scherrer, C. Thieke, H. Trinkaus

Intensity-Modulated Radiotherapy - A Large Scale Multi-Criteria Programming Problem Keywords: multiple criteria optimization, representative systems of Pareto solutions, adaptive triangulation, clustering and disaggregation techniques, visualization of Pareto solutions, medical physics, external beam radiotherapy planning, intensity modulated radiotherapy (31 pages, 2003)

### 44. T. Halfmann, T. Wichmann

## Overview of Symbolic Methods in Industrial Analog Circuit Design

Keywords: CAD, automated analog circuit design, symbolic analysis, computer algebra, behavioral modeling, system simulation, circuit sizing, macro modeling, differential-algebraic equations, index (17 pages, 2003)

#### 45. S. E. Mikhailov, J. Orlik

# Asymptotic Homogenisation in Strength and Fatigue Durability Analysis of Composites

Keywords: multiscale structures, asymptotic homogenization, strength, fatigue, singularity, non-local conditions

(14 pages, 2003)

46. P. Domínguez-Marín, P. Hansen, N. Mladenovic , S. Nickel

### Heuristic Procedures for Solving the Discrete Ordered Median Problem

Keywords: genetic algorithms, variable neighborhood search, discrete facility location (31 pages, 2003)

47. N. Boland, P. Domínguez-Marín, S. Nickel, I. Puerto

#### Exact Procedures for Solving the Discrete Ordered Median Problem

Keywords: discrete location, Integer programming (41 pages, 2003)

## 48. S. Feldmann, P. Lang

## Padé-like reduction of stable discrete linear systems preserving their stability

Keywords: Discrete linear systems, model reduction, stability, Hankel matrix, Stein equation (16 pages, 2003)

## 49. J. Kallrath, S. Nickel

### A Polynomial Case of the Batch Presorting Problem

Keywords: batch presorting problem, online optimization, competetive analysis, polynomial algorithms, logistics (17 pages, 2003)

### 50. T. Hanne, H. L. Trinkaus

### knowCube for MCDM – Visual and Interactive Support for Multicriteria Decision Making

Key words: Multicriteria decision making, knowledge management, decision support systems, visual interfaces, interactive navigation, real-life applications. (26 pages, 2003)

## 51. O. Iliev, V. Laptev

#### On Numerical Simulation of Flow Through Oil Filters

Keywords: oil filters, coupled flow in plain and porous media, Navier-Stokes, Brinkman, numerical simulation (8 pages, 2003)

## 52. W. Dörfler, O. Iliev, D. Stoyanov, D. Vassileva *On a Multigrid Adaptive Refinement Solver*

#### On a Multigrid Adaptive Refinement Solver for Saturated Non-Newtonian Flow in Porous Media

Keywords: Nonlinear multigrid, adaptive refinement, non-Newtonian flow in porous media (17 pages, 2003)

### 53. S. Kruse

## On the Pricing of Forward Starting Options under Stochastic Volatility

Keywords: Option pricing, forward starting options, Heston model, stochastic volatility, cliquet options (11 pages, 2003)

### 54. O. Iliev, D. Stoyanov

## Multigrid – adaptive local refinement solver for incompressible flows

Keywords: Navier-Stokes equations, incompressible flow, projection-type splitting, SIMPLE, multigrid methods, adaptive local refinement, lid-driven flow in a cavity (37 pages, 2003)

### 55. V. Starikovicius

## The multiphase flow and heat transfer in porous media

Keywords: Two-phase flow in porous media, various formulations, global pressure, multiphase mixture model, numerical simulation (30 pages, 2003)

## 56. P. Lang, A. Sarishvili, A. Wirsen

## Blocked neural networks for knowledge extraction in the software development process

Keywords: Blocked Neural Networks, Nonlinear Regression, Knowledge Extraction, Code Inspection (21 pages, 2003)

### 57. H. Knaf, P. Lang, S. Zeiser

## Diagnosis aiding in Regulation Thermography using Fuzzy Logic

Keywords: fuzzy logic,knowledge representation, expert system (22 pages, 2003)

## 58. M. T. Melo, S. Nickel, F. Saldanha da Gama Largescale models for dynamic multicommodity capacitated facility location

Keywords: supply chain management, strategic planning, dynamic location, modeling (40 pages, 2003)

## 59. J. Orlik

## Homogenization for contact problems with periodically rough surfaces

Keywords: asymptotic homogenization, contact problems (28 pages, 2004)

## 60. A. Scherrer, K.-H. Küfer, M. Monz, F. Alonso, T. Bortfeld

## IMRT planning on adaptive volume structures – a significant advance of computational complexity

Keywords: Intensity-modulated radiation therapy (IMRT), inverse treatment planning, adaptive volume structures, hierarchical clustering, local refinement, adaptive clustering, convex programming, mesh generation, multi-grid methods (24 pages, 2004)

## 61. D. Kehrwald

## Parallel lattice Boltzmann simulation of complex flows

Keywords: Lattice Boltzmann methods, parallel computing, microstructure simulation, virtual material design, pseudo-plastic fluids, liquid composite moulding (12 pages, 2004)

## 62. O. Iliev, J. Linn, M. Moog, D. Niedziela, V. Starikovicius

## On the Performance of Certain Iterative Solvers for Coupled Systems Arising in Discretization of Non-Newtonian Flow Equations

Keywords: Performance of iterative solvers, Preconditioners, Non-Newtonian flow (17 pages, 2004)

## 63. R. Ciegis, O. Iliev, S. Rief, K. Steiner

## On Modelling and Simulation of Different Regimes for Liquid Polymer Moulding

Keywords: Liquid Polymer Moulding, Modelling, Simulation, Infiltration, Front Propagation, non-Newtonian flow in porous media (43 pages, 2004)

### 64. T. Hanne, H. Neu

## Simulating Human Resources in Software Development Processes

Keywords: Human resource modeling, software process, productivity, human factors, learning curve (14 pages, 2004)

### 65. O. Iliev, A. Mikelic, P. Popov

## Fluid structure interaction problems in deformable porous media: Toward permeability of deformable porous media

Keywords: fluid-structure interaction, deformable porous media, upscaling, linear elasticity, stokes, finite elements

(28 pages, 2004)

## 66. F. Gaspar, O. Iliev, F. Lisbona, A. Naumovich, P. Vabishchevich

## On numerical solution of 1-D poroelasticity equations in a multilayered domain

Keywords: poroelasticity, multilayered material, finite volume discretization, MAC type grid (41 pages, 2004)

## 67. J. Ohser, K. Schladitz, K. Koch, M. Nöthe Diffraction by image processing and its application in materials science

Keywords: porous microstructure, image analysis, random set, fast Fourier transform, power spectrum, Bartlett spectrum (13 pages, 2004)

### 68. H. Neunzert

## Mathematics as a Technology: Challenges for the next 10 Years

Keywords: applied mathematics, technology, modelling, simulation, visualization, optimization, glass processing, spinning processes, fiber-fluid interaction, trubulence effects, topological optimization, multicriteria optimization, Uncertainty and Risk, financial mathematics, Malliavin calculus, Monte-Carlo methods, virtual material design, filtration, bio-informatics, system biology (29 pages, 2004)

# 69. R. Ewing, O. Iliev, R. Lazarov, A. Naumovich On convergence of certain finite difference discretizations for 1D poroelasticity interface problems

Keywords: poroelasticity, multilayered material, finite volume discretizations, MAC type grid, error estimates (26 pages, 2004)

## 70. W. Dörfler, O. Iliev, D. Stoyanov, D. Vassileva On Efficient Simulation of Non-Newtonian Flow in Saturated Porous Media with a Multigrid Adaptive Refinement Solver

Keywords: Nonlinear multigrid, adaptive renement, non-Newtonian in porous media (25 pages, 2004)

## 71. J. Kalcsics, S. Nickel, M. Schröder

## Towards a Unified Territory Design Approach – Applications, Algorithms and GIS Integration

Keywords: territory desgin, political districting, sales territory alignment, optimization algorithms, Geographical Information Systems (40 pages, 2005) 72. K. Schladitz, S. Peters, D. Reinel-Bitzer, A. Wiegmann, J. Ohser

## Design of acoustic trim based on geometric modeling and flow simulation for non-woven

Keywords: random system of fibers, Poisson line process, flow resistivity, acoustic absorption, Lattice-Boltzmann method, non-woven (21 pages, 2005)

### 73. V. Rutka, A. Wiegmann

# Explicit Jump Immersed Interface Method for virtual material design of the effective elastic moduli of composite materials

Keywords: virtual material design, explicit jump immersed interface method, effective elastic moduli, composite materials (22 pages, 2005)

#### 74. T. Hanne

## Eine Übersicht zum Scheduling von Baustellen

Keywords: Projektplanung, Scheduling, Bauplanung, Bauindustrie (32 pages, 2005)

### 75. J. Linn

## The Folgar-Tucker Model as a Differetial Algebraic System for Fiber Orientation Calculation

Keywords: fiber orientation, Folgar–Tucker model, invariants, algebraic constraints, phase space, trace stability

(15 pages, 2005)

## 76. M. Speckert, K. Dreßler, H. Mauch, A. Lion, G. J. Wierda

## Simulation eines neuartigen Prüfsystems für Achserprobungen durch MKS-Modellierung einschließlich Regelung

Keywords: virtual test rig, suspension testing, multibody simulation, modeling hexapod test rig, optimization of test rig configuration (20 pages, 2005)

 K.-H. Küfer, M. Monz, A. Scherrer, P. Süss, F. Alonso, A. S. A. Sultan, Th. Bortfeld, D. Craft, Chr. Thieke

## Multicriteria optimization in intensity modulated radiotherapy planning

Keywords: multicriteria optimization, extreme solutions, real-time decision making, adaptive approximation schemes, clustering methods, IMRT planning, reverse engineering (51 pages, 2005)

### 78. S. Amstutz, H. Andrä

## A new algorithm for topology optimization using a level-set method

Keywords: shape optimization, topology optimization, topological sensitivity, level-set (22 pages, 2005)

### 79. N. Ettrich

## Generation of surface elevation models for urban drainage simulation

Keywords: Flooding, simulation, urban elevation models, laser scanning (22 pages, 2005)

### 80. H. Andrä, J. Linn, I. Matei, I. Shklyar, K. Steiner, E. Teichmann

## OPTCAST – Entwicklung adäquater Strukturoptimierungsverfahren für Gießereien Technischer Bericht (KURZFASSUNG)

Keywords: Topologieoptimierung, Level-Set-Methode, Gießprozesssimulation, Gießtechnische Restriktionen, CAE-Kette zur Strukturoptimierung (77 pages, 2005)

## 81. N. Marheineke, R. Wegener

## Fiber Dynamics in Turbulent Flows Part I: General Modeling Framework

Keywords: fiber-fluid interaction; Cosserat rod; turbulence modeling; Kolmogorov's energy spectrum; double-velocity correlations; differentiable Gaussian fields (20 pages, 2005)

## Part II: Specific Taylor Drag

Keywords: flexible fibers; k-ε turbulence model; fiber-turbulence interaction scales; air drag; random Gaussian aerodynamic force; white noise; stochastic differential equations; ARMA process (18 pages, 2005)

## 82. C. H. Lampert, O. Wirjadi

### An Optimal Non-Orthogonal Separation of the Anisotropic Gaussian Convolution Filter Keywords: Anisotropic Gaussian filter, linear filtering, ori-

entation space, nD image processing, separable filters (25 pages, 2005)

## 83. H. Andrä, D. Stoyanov

## Error indicators in the parallel finite element solver for linear elasticity DDFEM

Keywords: linear elasticity, finite element method, hierarchical shape functions, domain decom-position, parallel implementation, a posteriori error estimates (21 pages, 2006)

## 84. M. Schröder, I. Solchenbach

## Optimization of Transfer Quality in Regional Public Transit

Keywords: public transit, transfer quality, quadratic assignment problem (16 pages, 2006)

### 85. A. Naumovich, F. J. Gaspar

## On a multigrid solver for the three-dimensional Biot poroelasticity system in multilayered domains

Keywords: poroelasticity, interface problem, multigrid, operator-dependent prolongation (11 pages, 2006)

## 86. S. Panda, R. Wegener, N. Marheineke Slender Body Theory for the Dynamics of Curved Viscous Fibers

Keywords: curved viscous fibers; fluid dynamics; Navier-Stokes equations; free boundary value problem; asymptotic expansions; slender body theory (14 pages, 2006)

### 87. E. Ivanov, H. Andrä, A. Kudryavtsev

## Domain Decomposition Approach for Automatic Parallel Generation of Tetrahedral Grids

Key words: Grid Generation, Unstructured Grid, Delaunay Triangulation, Parallel Programming, Domain Decomposition, Load Balancing (18 pages, 2006)

## 88. S. Tiwari, S. Antonov, D. Hietel, J. Kuhnert, R. Wegener

## A Meshfree Method for Simulations of Interactions between Fluids and Flexible Structures

Key words: Meshfree Method, FPM, Fluid Structure Interaction, Sheet of Paper, Dynamical Coupling (16 pages, 2006)

## 89. R. Ciegis , O. Iliev, V. Starikovicius, K. Steiner Numerical Algorithms for Solving Problems of Multiphase Flows in Porous Media

Keywords: nonlinear algorithms, finite-volume method, software tools, porous media, flows (16 pages, 2006)

90. D. Niedziela, O. Iliev, A. Latz

## On 3D Numerical Simulations of Viscoelastic

Keywords: non-Newtonian fluids, anisotropic viscosity, integral constitutive equation (18 pages, 2006)

#### 91. A. Winterfeld

## Application of general semi-infinite Programming to Lapidary Cutting Problems

Keywords: large scale optimization, nonlinear programming, general semi-infinite optimization, design centering, clustering (26 pages, 2006)

### 92. J. Orlik, A. Ostrovska

## Space-Time Finite Element Approximation and Numerical Solution of Hereditary Linear Viscoelasticity Problems

Keywords: hereditary viscoelasticity; kern approximation by interpolation; space-time finite element approximation, stability and a priori estimate (24 pages, 2006)

## 93. V. Rutka, A. Wiegmann, H. Andrä EJIIM for Calculation of effective Elastic Moduli in 3D Linear Elasticity

Keywords: Elliptic PDE, linear elasticity, irregular domain, finite differences, fast solvers, effective elastic moduli (24 pages, 2006)

#### 94. A. Wiegmann, A. Zemitis

### EJ-HEAT: A Fast Explicit Jump Harmonic Averaging Solver for the Effective Heat Conductivity of Composite Materials

Keywords: Stationary heat equation, effective thermal conductivity, explicit jump, discontinuous coefficients, virtual material design, microstructure simulation, EJ-HEAT (21 pages, 2006)

### 95. A. Naumovich

## On a finite volume discretization of the three-dimensional Biot poroelasticity system in multilayered domains

Keywords: Biot poroelasticity system, interface problems, finite volume discretization, finite difference method (21 pages, 2006)

### 96. M. Krekel, J. Wenzel

## A unified approach to Credit Default Swaption and Constant Maturity Credit Default Swap valuation

Keywords: LIBOR market model, credit risk, Credit Default Swaption, Constant Maturity Credit Default Swapmethod (43 pages, 2006)

## 97. A. Dreyer

## Interval Methods for Analog Circiuts

Keywords: interval arithmetic, analog circuits, tolerance analysis, parametric linear systems, frequency response, symbolic analysis, CAD, computer algebra (36 pages, 2006)

## 98. N. Weigel, S. Weihe, G. Bitsch, K. Dreßler Usage of Simulation for Design and Optimization of Testing

Keywords: Vehicle test rigs, MBS, control, hydraulics, testing philosophy (14 pages, 2006)

# 99. H. Lang, G. Bitsch, K. Dreßler, M. Speckert Comparison of the solutions of the elastic and elastoplastic boundary value problems

Keywords: Elastic BVP, elastoplastic BVP, variational inequalities, rate-independency, hysteresis, linear kinematic hardening, stop- and play-operator (21 pages, 2006)

## 100. M. Speckert, K. Dreßler, H. Mauch MBS Simulation of a hexapod based suspension test rig

Keywords: Test rig, MBS simulation, suspension, hydraulics, controlling, design optimization (12 pages, 2006)

## 101. S. Azizi Sultan, K.-H. Küfer

## A dynamic algorithm for beam orientations in multicriteria IMRT planning

Keywords: radiotherapy planning, beam orientation optimization, dynamic approach, evolutionary algorithm, global optimization (14 pages, 2006)

## 102. T. Götz, A. Klar, N. Marheineke, R. Wegener A Stochastic Model for the Fiber Lay-down Process in the Nonwoven Production

Keywords: fiber dynamics, stochastic Hamiltonian system, stochastic averaging (17 pages, 2006)

#### 103. Ph. Süss, K.-H. Küfer

# Balancing control and simplicity: a variable aggregation method in intensity modulated radiation therapy planning

Keywords: IMRT planning, variable aggregation, clustering methods (22 pages, 2006)

# 104. A. Beaudry, G. Laporte, T. Melo, S. Nickel *Dynamic transportation of patients in hospitals*

Keywords: in-house hospital transportation, dial-a-ride, dynamic mode, tabu search (37 pages, 2006)

### 105. Th. Hanne

## Applying multiobjective evolutionary algorithms in industrial projects

Keywords: multiobjective evolutionary algorithms, discrete optimization, continuous optimization, electronic circuit design, semi-infinite programming, scheduling (18 pages, 2006)

## 106. J. Franke, S. Halim

## Wild bootstrap tests for comparing signals and images

Keywords: wild bootstrap test, texture classification, textile quality control, defect detection, kernel estimate, nonparametric regression (13 pages, 2007)

## 107. Z. Drezner, S. Nickel

## Solving the ordered one-median problem in the plane

Keywords: planar location, global optimization, ordered median, big triangle small triangle method, bounds, numerical experiments (21 pages, 2007)

## 108. Th. Götz, A. Klar, A. Unterreiter,

### Numerical evidance for the non-existing of solutions of the equations desribing rotational fiber spinning

Keywords: rotational fiber spinning, viscous fibers, boundary value problem, existence of solutions (11 pages, 2007) 109. Ph. Süss, K.-H. Küfer

## Smooth intensity maps and the Bortfeld-Boyer sequencer

Keywords: probabilistic analysis, intensity modulated radiotherapy treatment (IMRT), IMRT plan application, step-and-shoot sequencing (8 pages, 2007)

### 110. E. Ivanov, O. Gluchshenko, H. Andrä, A. Kudryavtsev

## Parallel software tool for decomposing and meshing of 3d structures

Keywords: a-priori domain decomposition, unstructured grid, Delaunay mesh generation (14 pages, 2007)

### 111. O. Iliev, R. Lazarov, J. Willems

## Numerical study of two-grid preconditioners for 1d elliptic problems with highly oscillating discontinuous coefficients

Keywords: two-grid algorithm, oscillating coefficients, preconditioner (20 pages, 2007)

## 112. L. Bonilla, T. Götz, A. Klar, N. Marheineke, R. Wegener

## Hydrodynamic limit of the Fokker-Planckequation describing fiber lay-down processes

Keywords: stochastic dierential equations, Fokker-Planck equation, asymptotic expansion, Ornstein-Uhlenbeck process (17 pages, 2007)

#### 113. S. Rief

## Modeling and simulation of the pressing section of a paper machine

Keywords: paper machine, computational fluid dynamics, porous media (41 pages, 2007)

## 114. R. Ciegis, O. Iliev, Z. Lakdawala

## On parallel numerical algorithms for simulating industrial filtration problems

Keywords: Navier-Stokes-Brinkmann equations, finite volume discretization method, SIMPLE, parallel computing, data decomposition method (24 pages, 2007)

## 115. N. Marheineke, R. Wegener

## Dynamics of curved viscous fibers with surface tension

Keywords: Slender body theory, curved viscous bers with surface tension, free boundary value problem (25 pages, 2007)

## 116. S. Feth, J. Franke, M. Speckert

## Resampling-Methoden zur mse-Korrektur und Anwendungen in der Betriebsfestigkeit

Keywords: Weibull, Bootstrap, Maximum-Likelihood, Betriebsfestigkeit (16 pages, 2007)

## 117. H. Knaf

## Kernel Fisher discriminant functions – a concise and rigorous introduction

Keywords: wild bootstrap test, texture classification, textile quality control, defect detection, kernel estimate, nonparametric regression (30 pages, 2007)

## 118. O. Iliev, I. Rybak

## On numerical upscaling for flows in heterogeneous porous media

Keywords: numerical upscaling, heterogeneous porous media, single phase flow, Darcy's law, multiscale problem, effective permeability, multipoint flux approximation, anisotropy

(17 pages, 2007)

### 119. O. Iliev, I. Rybak

### On approximation property of multipoint flux approximation method

Keywords: Multipoint flux approximation, finite volume method, elliptic equation, discontinuous tensor coefficients, anisotropy (15 pages, 2007)

#### 120. O. Iliev, I. Rybak, J. Willems

### On upscaling heat conductivity for a class of industrial problems

Keywords: Multiscale problems, effective heat conductivity, numerical upscaling, domain decomposition (21 pages, 2007)

## 121. R. Ewing, O. Iliev, R. Lazarov, I. Rybak On two-level preconditioners for flow in porous media

Keywords: Multiscale problem, Darcy's law, single phase flow, anisotropic heterogeneous porous media, numerical upscaling, multigrid, domain decomposition, efficient preconditioner (18 pages, 2007)

### 122. M. Brickenstein, A. Dreyer

## POLYBORI: A Gröbner basis framework for Boolean polynomials

Keywords: Gröbner basis, formal verification, Boolean polynomials, algebraic cryptoanalysis, satisfiability (23 pages, 2007)

#### 123. O. Wirjadi

### Survey of 3d image segmentation methods

Keywords: image processing, 3d, image segmentation, binarization (20 pages, 2007)

### 124. S. Zeytun, A. Gupta

## A Comparative Study of the Vasicek and the CIR Model of the Short Rate

Keywords: interest rates, Vasicek model, CIR-model, calibration, parameter estimation (17 pages, 2007)

### 125. G. Hanselmann, A. Sarishvili

### Heterogeneous redundancy in software quality prediction using a hybrid Bayesian approach

Keywords: reliability prediction, fault prediction, nonhomogeneous poisson process, Bayesian model aver-

(17 pages, 2007)

## 126. V. Maag, M. Berger, A. Winterfeld, K.-H.

## A novel non-linear approach to minimal area rectangular packing

Keywords: rectangular packing, non-overlapping constraints, non-linear optimization, regularization, relax-

(18 pages, 2007)

## 127. M. Monz, K.-H. Küfer, T. Bortfeld, C. Thieke Pareto navigation - systematic multi-criteria-based IMRT treatment plan determination

Keywords: convex, interactive multi-objective optimization, intensity modulated radiotherapy planning (15 pages, 2007)

### 128. M. Krause, A. Scherrer

## On the role of modeling parameters in IMRT plan optimization

Keywords: intensity-modulated radiotherapy (IMRT), inverse IMRT planning, convex optimization, sensitivity analysis, elasticity, modeling parameters, equivalent uniform dose (EUD) (18 pages, 2007)

#### 129. A. Wiegmann

## Computation of the permeability of porous materials from their microstructure by FFF-Stokes

Keywords: permeability, numerical homogenization, fast Stokes solver (24 pages, 2007)

## 130. T. Melo, S. Nickel, F. Saldanha da Gama Facility Location and Supply Chain Management - A comprehensive review

Keywords: facility location, supply chain management, network design (54 pages, 2007)

## 131. T. Hanne, T. Melo, S. Nickel

## Bringing robustness to patient flow management through optimized patient transports in hospitals

Keywords: Dial-a-Ride problem, online problem, case study, tabu search, hospital logistics (23 pages, 2007)

## 132. R. Ewing, O. Iliev, R. Lazarov, I. Rybak, J. Willems

### An efficient approach for upscaling properties of composite materials with high contrast of coefficients

Keywords: effective heat conductivity, permeability of fractured porous media, numerical upscaling, fibrous insulation materials, metal foams (16 pages, 2008)

### 133. S. Gelareh, S. Nickel

## New approaches to hub location problems in public transport planning

Keywords: integer programming, hub location, transportation, decomposition, heuristic (25 pages, 2008)

134. G. Thömmes, J. Becker, M. Junk, A. K. Vaikuntam, D. Kehrwald, A. Klar, K. Steiner, A. Wiegmann

### A Lattice Boltzmann Method for immiscible multiphase flow simulations using the Level Set Method

Keywords: Lattice Boltzmann method, Level Set method, free surface, multiphase flow (28 pages, 2008)

### 135. J. Orlik

## Homogenization in elasto-plasticity

Keywords: multiscale structures, asymptotic homogenization, nonlinear energy (40 pages, 2008)

## 136. J. Almquist, H. Schmidt, P. Lang, J. Deitmer, M. Jirstrand, D. Prätzel-Wolters, H. Becker

## Determination of interaction between MCT1 and CAII via a mathematical and physiological approach

Keywords: mathematical modeling; model reduction; electrophysiology; pH-sensitive microelectrodes; proton antenna (20 pages, 2008)

137. E. Savenkov, H. Andrä, O. Iliev

## An analysis of one regularization approach for solution of pure Neumann problem

Keywords: pure Neumann problem, elasticity, regularization, finite element method, condition number (27 pages, 2008)

## 138. O. Berman, J. Kalcsics, D. Krass, S. Nickel The ordered gradual covering location problem on a network

Keywords: gradual covering, ordered median function, network location (32 pages, 2008)

## 139. S. Gelareh, S. Nickel

## Multi-period public transport design: A novel model and solution approaches

Keywords: Integer programming, hub location, public transport, multi-period planning, heuristics (31 pages, 2008)

## 140. T. Melo, S. Nickel, F. Saldanha-da-Gama Network design decisions in supply chain planning

Keywords: supply chain design, integer programming models, location models, heuristics (20 pages, 2008)

141. C. Lautensack, A. Särkkä, J. Freitag, K. Schladitz

## Anisotropy analysis of pressed point pro-

Keywords: estimation of compression, isotropy test, nearest neighbour distance, orientation analysis, polar ice, Ripley's K function (35 pages, 2008)

### 142. O. Iliev, R. Lazarov, J. Willems

## A Graph-Laplacian approach for calculating the effective thermal conductivity of complicated fiber geometries

Keywords: graph laplacian, effective heat conductivity, numerical upscaling, fibrous materials (14 pages, 2008)

### 143. J. Linn, T. Stephan, J. Carlsson, R. Bohlin Fast simulation of quasistatic rod deformations for VR applications

Keywords: quasistatic deformations, geometrically exact rod models, variational formulation, energy minimization, finite differences, nonlinear conjugate gradients

(7 pages, 2008)

### 144. J. Linn, T. Stephan

## Simulation of quasistatic deformations using discrete rod models

Keywords: quasistatic deformations, geometrically exact rod models, variational formulation, energy minimization, finite differences, nonlinear conjugate gra-

(9 pages, 2008)

### 145. J. Marburger, N. Marheineke, R. Pinnau Adjoint based optimal control using meshless discretizations

Keywords: Mesh-less methods, particle methods, Eulerian-Lagrangian formulation, optimization strategies, adjoint method, hyperbolic equations (14 pages, 2008

## 146. S. Desmettre, J. Gould, A. Szimayer

## Own-company stockholding and work effort preferences of an unconstrained executive

Keywords: optimal portfolio choice, executive compensation

(33 pages, 2008)

toopiciilie

147. M. Berger, M. Schröder, K.-H. Küfer

## A constraint programming approach for the two-dimensional rectangular packing problem with orthogonal orientations

Keywords: rectangular packing, orthogonal orientations non-overlapping constraints, constraint propagation

(13 pages, 2008)

148. K. Schladitz, C. Redenbach, T. Sych, M. Godehardt

## Microstructural characterisation of open foams using 3d images

Keywords: virtual material design, image analysis, open foams

(30 pages, 2008)

149. E. Fernández, J. Kalcsics, S. Nickel, R. Ríos-Mercado

## A novel territory design model arising in the implementation of the WEEE-Directive

Keywords: heuristics, optimization, logistics, recycling (28 pages, 2008)

150. H. Lang, J. Linn

## Lagrangian field theory in space-time for geometrically exact Cosserat rods

Keywords: Cosserat rods, geometrically exact rods, small strain, large deformation, deformable bodies, Lagrangian field theory, variational calculus (19 pages, 2009)

151. K. Dreßler, M. Speckert, R. Müller, Ch. Weber

## Customer loads correlation in truck engineering

Keywords: Customer distribution, safety critical components, quantile estimation, Monte-Carlo methods (11 pages, 2009)

152. H. Lang, K. Dreßler

## An improved multiaxial stress-strain correction model for elastic FE postprocessing

Keywords: Jiang's model of elastoplasticity, stress-strain correction, parameter identification, automatic differentiation, least-squares optimization, Coleman-Li algorithm

(6 pages, 2009)

153. J. Kalcsics, S. Nickel, M. Schröder

## A generic geometric approach to territory design and districting

Keywords: Territory design, districting, combinatorial optimization, heuristics, computational geometry (32 pages, 2009)

154. Th. Fütterer, A. Klar, R. Wegener

## An energy conserving numerical scheme for the dynamics of hyperelastic rods

Keywords: Cosserat rod, hyperealstic, energy conservation, finite differences (16 pages, 2009)

155. A. Wiegmann, L. Cheng, E. Glatt, O. Iliev, S. Rief

## Design of pleated filters by computer simulations

Keywords: Solid-gas separation, solid-liquid separation, pleated filter, design, simulation (21 pages, 2009)

156. A. Klar, N. Marheineke, R. Wegener Hierarchy of mathematical models for production processes of technical textiles Keywords: Fiber-fluid interaction, slender-body theory, turbulence modeling, model reduction, stochastic differential equations, Fokker-Planck equation, asymptotic expansions, parameter identification (21 pages, 2009)

157. E. Glatt, S. Rief, A. Wiegmann, M. Knefel, E. Wegenke

## Structure and pressure drop of real and virtual metal wire meshes

Keywords: metal wire mesh, structure simulation, model calibration, CFD simulation, pressure loss (7 pages, 2009)

158. S. Kruse, M. Müller

## Pricing American call options under the assumption of stochastic dividends – An application of the Korn-Rogers model

Keywords: option pricing, American options, dividends, dividend discount model, Black-Scholes model (22 pages, 2009)

159. H. Lang, J. Linn, M. Arnold

## Multibody dynamics simulation of geometrically exact Cosserat rods

Keywords: flexible multibody dynamics, large deformations, finite rotations, constrained mechanical systems, structural dynamics (20 pages, 2009)

## 160. P. Jung, S. Leyendecker, J. Linn, M. Ortiz Discrete Lagrangian mechanics and geometrically exact Cosserat rods

Keywords: special Cosserat rods, Lagrangian mechanics, Noether's theorem, discrete mechanics, frame-indifference, holonomic constraints (14 pages, 2009)

161. M. Burger, K. Dreßler, A. Marquardt, M. Speckert

## Calculating invariant loads for system simulation in vehicle engineering

Keywords: iterative learning control, optimal control theory, differential algebraic equations (DAEs) (18 pages, 2009)

162. M. Speckert, N. Ruf, K. Dreßler

## Undesired drift of multibody models excited by measured accelerations or forces

Keywords: multibody simulation, full vehicle model, force-based simulation, drift due to noise (19 pages, 2009)

163. A. Streit, K. Dreßler, M. Speckert, J. Lichter, T. Zenner, P. Bach

## Anwendung statistischer Methoden zur Erstellung von Nutzungsprofilen für die Auslegung von Mobilbaggern

Keywords: Nutzungsvielfalt, Kundenbeanspruchung, Bemessungsgrundlagen (13 pages, 2009)

# 164. I. Correia, S. Nickel, F. Saldanha-da-Gama *The capacitated single-allocation hub location problem revisited: A note on a classical formulation*

Keywords: Capacitated Hub Location, MIP formulations (10 pages, 2009)

165. F. Yaneva, T. Grebe, A. Scherrer

## An alternative view on global radiotherapy optimization problems

Keywords: radiotherapy planning, path-connected sublevelsets, modified gradient projection method, improving and feasible directions (14 pages, 2009) 166. J. I. Serna, M. Monz, K.-H. Küfer, C. Thieke Trade-off bounds and their effect in multicriteria IMRT planning

Keywords: trade-off bounds, multi-criteria optimization, IMRT, Pareto surface (15 pages, 2009)

167. W. Arne, N. Marheineke, A. Meister, R. Wegener

## Numerical analysis of Cosserat rod and string models for viscous jets in rotational spinning processes

Keywords: Rotational spinning process, curved viscous fibers, asymptotic Cosserat models, boundary value problem, existence of numerical solutions (18 pages, 2009)

## 168. T. Melo, S. Nickel, F. Saldanha-da-Gama An LP-rounding heuristic to solve a multiperiod facility relocation problem

Keywords: supply chain design, heuristic, linear programming, rounding (37 pages, 2009)

## 169. I. Correia, S. Nickel, F. Saldanha-da-Gama Single-allocation hub location problems with capacity choices

Keywords: hub location, capacity decisions, MILP formulations (27 pages, 2009)

170. S. Acar, K. Natcheva-Acar

## A guide on the implementation of the Heath-Jarrow-Morton Two-Factor Gaussian Short Rate Model (HJM-G2++)

Keywords: short rate model, two factor Gaussian, G2++, option pricing, calibration (30 pages, 2009)

171. A. Szimayer, G. Dimitroff, S. Lorenz

## A parsimonious multi-asset Heston model: calibration and derivative pricing

Keywords: Heston model, multi-asset, option pricing, calibration, correlation (28 pages, 2009)

### 172. N. Marheineke, R. Wegener

## Modeling and validation of a stochastic drag for fibers in turbulent flows

Keywords: fiber-fluid interactions, long slender fibers, turbulence modelling, aerodynamic drag, dimensional analysis, data interpolation, stochastic partial differential algebraic equation, numerical simulations, experimental validations (19 pages, 2009)

173. S. Nickel, M. Schröder, J. Steeg

### Planning for home health care services

Keywords: home health care, route planning, metaheuristics, constraint programming (23 pages, 2009)

## 174. G. Dimitroff, A. Szimayer, A. Wagner Quanto option pricing in the parsimonious Heston model

Keywords: Heston model, multi asset, quanto options, option pricing (14 pages, 2009) 174. G. Dimitroff, A. Szimayer, A.

(14 pages, 2009) 174. G. Dimitroff, A. Szimayer, A Wagner

## 175. S. Herkt, K. Dreßler, R. Pinnau *Model reduction of nonlinear problems in*

## structural mechanics

Keywords: flexible bodies, FEM, nonlinear model reduction, POD (13 pages, 2009)

## 176. M. K. Ahmad, S. Didas, J. Iqbal

## Using the Sharp Operator for edge detection and nonlinear diffusion

Keywords: maximal function, sharp function,image processing, edge detection, nonlinear diffusion (17 pages, 2009)

177. M. Speckert, N. Ruf, K. Dreßler, R. Müller, C. Weber, S. Weihe

### Ein neuer Ansatz zur Ermittlung von Erprobungslasten für sicherheitsrelevante Bauteile

Keywords: sicherheitsrelevante Bauteile, Kundenbeanspruchung, Festigkeitsverteilung, Ausfallwahrscheinlichkeit, Konfidenz, statistische Unsicherheit, Sicherheitsfaktoren (16 pages, 2009)

#### 178. J. Jegorovs

### Wave based method: new applicability areas

Keywords: Elliptic boundary value problems, inhomogeneous Helmholtz type differential equations in bounded domains, numerical methods, wave based method, uniform B-splines (10 pages, 2009)

#### 179. H. Lang, M. Arnold

## Numerical aspects in the dynamic simulation of geometrically exact rods

Keywords: Kirchhoff and Cosserat rods, geometrically exact rods, deformable bodies, multibody dynamics, artial differential algebraic equations, method of lines, time integration (21 pages, 2009)

## 180. H. Lang

## Comparison of quaternionic and rotationfree null space formalisms for multibody dynamics

Keywords: Parametrisation of rotations, differentialalgebraic equations, multibody dynamics, constrained mechanical systems, Lagrangian mechanics (40 pages, 2010)

# 181. S. Nickel, F. Saldanha-da-Gama, H.-P. Ziegler Stochastic programming approaches for risk aware supply chain network design problems

Keywords: Supply Chain Management, multi-stage stochastic programming, financial decisions, risk (37 pages, 2010)

## 182. P. Ruckdeschel, N. Horbenko

## Robustness properties of estimators in generalized Pareto Models

Keywords: global robustness, local robustness, finite sample breakdown point, generalized Pareto distribution (58 pages, 2010)

## 183. P. Jung, S. Leyendecker, J. Linn, M. Ortiz

## A discrete mechanics approach to Cosserat rod theory – Part 1: static equilibria

Keywords: Special Cosserat rods; Lagrangian mechanics; Noether's theorem; discrete mechanics; frame-indifference; holonomic constraints; variational formulation

(35 pages, 2010)

## 184. R. Eymard, G. Printsypar

## A proof of convergence of a finite volume scheme for modified steady Richards' equation describing transport processes in the pressing section of a paper machine

Keywords: flow in porous media, steady Richards' equation, finite volume methods, convergence of approximate solution (14 pages, 2010)

185. P. Ruckdeschel

## Optimally Robust Kalman Filtering

Keywords: robustness, Kalman Filter, innovation outlier, additive outlier (42 pages, 2010)

# 186. S. Repke, N. Marheineke, R. Pinnau On adjoint-based optimization of a free surface Stokes flow

Keywords: film casting process, thin films, free surface Stokes flow, optimal control, Lagrange formalism (13 pages, 2010)

## 187. O. Iliev, R. Lazarov, J. Willems

## Variational multiscale Finite Element Method for flows in highly porous media

Keywords: numerical upscaling, flow in heterogeneous porous media, Brinkman equations, Darcy's law, subgrid approximation, discontinuous Galerkin mixed FEM (21 pages, 2010)

## 188. S. Desmettre, A. Szimayer

# Work effort, consumption, and portfolio selection: When the occupational choice matters

Keywords: portfolio choice, work effort, consumption, occupational choice (34 pages, 2010)

### 189. O. Iliev, Z. Lakdawala, V. Starikovicius

## On a numerical subgrid upscaling algorithm for Stokes-Brinkman equations

Keywords: Stokes-Brinkman equations, subgrid approach, multiscale problems, numerical upscaling (27 pages, 2010)

### 190. A. Latz, J. Zausch, O. Iliev

## Modeling of species and charge transport in Li-Ion Batteries based on non-equilibrium thermodynamics

Keywords: lithium-ion battery, battery modeling, electrochemical simulation, concentrated electrolyte, ion transport (8 pages, 2010)

# 191. P. Popov, Y. Vutov, S. Margenov, O. Iliev *Finite volume discretization of equations describing nonlinear diffusion in Li-Ion batteries*

Keywords: nonlinear diffusion, finite volume discretization, Newton method, Li-Ion batteries (9 pages, 2010)

## 192. W. Arne, N. Marheineke, R. Wegener

# Asymptotic transition from Cosserat rod to string models for curved viscous inertial jets

Keywords: rotational spinning processes; inertial and viscous-inertial fiber regimes; asymptotic limits; slender-body theory; boundary value problems (23 pages, 2010)

### 193. L. Engelhardt, M. Burger, G. Bitsch

## Real-time simulation of multibody-systems for on-board applications

Keywords: multibody system simulation, real-time simulation, on-board simulation, Rosenbrock methods (10 pages, 2010)

## 194. M. Burger, M. Speckert, K. Dreßler

# Optimal control methods for the calculation of invariant excitation signals for multibody systems

Keywords: optimal control, optimization, mbs simulation, invariant excitation (9 pages, 2010) 195. A. Latz, J. Zausch

## Thermodynamic consistent transport theory of Li-Ion batteries

Keywords: Li-Ion batteries, nonequilibrium thermodynamics, thermal transport, modeling (18 pages, 2010)

### 196. S. Desmettre

## Optimal investment for executive stockholders with exponential utility

Keywords: portfolio choice, executive stockholder, work effort, exponential utility (24 pages, 2010)

## 197. W. Arne, N. Marheineke, J. Schnebele, R. Wegener

## Fluid-fiber-interactions in rotational spinning process of glass wool production

Keywords: Rotational spinning process, viscous thermal jets, fluid-fiber-interactions, two-way coupling, slender-body theory, Cosserat rods, drag models, boundary value problem, continuation method (20 pages, 2010)

## 198. A. Klar, J. Maringer, R. Wegener

## A 3d model for fiber lay-down in nonwoven production processes

Keywords: fiber dynamics, Fokker-Planck equations, diffusion limits (15 pages, 2010)

#### 199. Ch. Erlwein, M. Müller

## A regime-switching regression model for hedge funds

Keywords: switching regression model, Hedge funds, optimal parameter estimation, filtering (26 pages, 2011)

#### 200. M. Dalheimer

## Power to the people – Das Stromnetz der Zukunft

Keywords: Smart Grid, Stromnetz, Erneuerbare Energien, Demand-Side Management (27 pages, 2011)

### 201. D. Stahl, J. Hauth

## PF-MPC: Particle Filter-Model Predictive Control

Keywords: Model Predictive Control, Particle Filter, CSTR, Inverted Pendulum, Nonlinear Systems, Sequential Monte Carlo (40 pages, 2011)

### 202. G. Dimitroff, J. de Kock

## Calibrating and completing the volatility cube in the SABR Model

Keywords: stochastic volatility, SABR, volatility cube, swaption (12 pages, 2011)

## 203. J.-P. Kreiss, T. Zangmeister

## Quantification of the effectiveness of a safety function in passenger vehicles on the basis of real-world accident data

Keywords: logistic regression, safety function, realworld accident data, statistical modeling (23 pages, 2011)

## 204. P. Ruckdeschel, T. Sayer, A. Szimayer

### Pricing American options in the Heston model: a close look on incorporating correlation

Keywords: Heston model, American options, moment matching, correlation, tree method (30 pages, 2011) 205. H. Ackermann, H. Ewe, K.-H. Küfer, M. Schröder

## Modeling profit sharing in combinatorial exchanges by network flows

Keywords: Algorithmic game theory, profit sharing, combinatorial exchange, network flows, budget balance, core (17 pages, 2011)

206. O. Iliev, G. Printsypar, S. Rief

## A one-dimensional model of the pressing section of a paper machine including dynamic capillary effects

Keywords: steady modified Richards' equation, finite volume method, dynamic capillary pressure, pressing section of a paper machine (29 pages, 2011)

207. I. Vecchio, K. Schladitz, M. Godehardt, M. J. Heneka

## Geometric characterization of particles in 3d with an application to technical cleanliness

Keywords: intrinsic volumes, isoperimetric shape factors, bounding box, elongation, geodesic distance, technical cleanliness (21 pages, 2011)

# 208. M. Burger, K. Dreßler, M. Speckert Invariant input loads for full vehicle multibody system simulation

Keywords: multibody systems, full-vehicle simulation, optimal control (8 pages, 2011)

209. H. Lang, J. Linn, M. Arnold

## Multibody dynamics simulation of geometrically exact Cosserat rods

Keywords: flexible multibody dynamics, large deformations, finite rotations, constrained mechanical systems, structural dynamics (28 pages, 2011)

210. G. Printsypar, R. Ciegis

## On convergence of a discrete problem describing transport processes in the pressing section of a paper machine including dynamic capillary effects: one-dimensional case

Keywords: saturated and unsaturated fluid flow in porous media, Richards' approach, dynamic capillary pressure, finite volume methods, convergence of approximate solution (24 pages, 2011)

## 211. O. Iliev, G. Printsypar, S. Rief

## A two-cimensional model of the pressing section of a paper machine including dynamic capillary effects

Keywords: two-phase flow in porous media, steady modified Richards' equation, finite volume method, dynamic capillary pressure, pressing section of a paper machine, multipoint flux approximation (44 pages, 2012)

## 212. M. Buck, O. Iliev, H. Andrä

## Multiscale finite element coarse spaces for the analysis of linear elastic composites

Keywords: linear elasticity, domain decomposition, multiscale finite elements, robust coarse spaces, rigid body modes, discontinuous coefficients (31 pages, 2012)

## 213. A. Wagner

## Residual demand modeling and application to electricity pricing

Keywords: residual demand modeling, renewable infeed, wind infeed, solar infeed, electricity demand, German power market, merit-order effect (28 pages, 2012) 214. O. Iliev, A. Latz, J. Zausch, S. Zhang

# An overview on the usage of some model reduction approaches for simulations of Liion transport in batteries

Keywords: Li-ion batteries, porous electrode model, model reduction (21 pages, 2012)

215. C. Zémerli, A. Latz, H. Andrä

## Constitutive models for static granular systems and focus to the Jiang-Liu hyperelastic law

Keywords: granular elasticity, constitutive modelling, non-linear finite element method (33 pages, 2012)

216. T. Gornak, J. L. Guermond, O. Iliev, P. D. Minev

## A direction splitting approach for incompressible Brinkmann flow

Keywords: unsteady Navier-Stokes-Brinkman equations, direction splitting algorithms, nuclear reactors safety simulations (16 pages, 2012)

217. Y. Efendiev, O. Iliev, C. Kronsbein

## Multi-level Monte Carlo methods using ensemble level mixed MsFEM for two-phase flow and transport simulations

Keywords: two phase flow in porous media, uncertainty quantification, multilevel Monte Carlo (28 pages, 2012)

Status quo: June 2012